

FLEXSTEEL FUTURA



Product Specification

Application

Flexsteel® Futura™ with Futurin™ cover resists cracking and fading, designed to dispense a wide range of fuels with extreme durability. The wire braid construction provides excellent kink resistance, low computer creep, and long service life. UL 330 and CUL approved.

Construction Tube

Nitrile synthetic rubber (ORS)

Cover

Futurin™ synthetic rubber (ORS)

Reinforcement

Wire braid

Temperature Range

-40 to 140

Packaging

5/8" and 3/4" Reels or coupled lengths, 10 pieces per box
 1" Reels or coupled lengths, 5 pieces per box

Branding

CONTINENTAL CONTITECH 3/4" (19.0MM) CRUUS FLEXSTEEL FUTURA GASOLINE HOSE 559N MADE IN USA

Coupling

Available as factory coupled assemblies only

Non Stock / Sizes

For special production run minimum requirements, see Appendix D.

Order Codes

532-327

FLEXSTEEL FUTURA

ID		NOM. OD		WEIGHT-INNER HOSE		WEIGHT	
in.	mm.	in.	mm.	lb./ft.	kg./m.	lb./ft.	kg./m.
5/8	15.9	1	25.4	0.4	0.6	0.4	0.6
3/4	19.1	1.13	28.7	0.45	0.67	0.45	0.67
1	25.4	1.38	35.1	0.61	0.91	0.61	0.91