


**670 Series** paulin METRIC HEX NUTS

PART CLASS #  
800AX | DIN 934 = ISO 4032



Use a HEX NUT with a screw or bolt to fasten two or more parts. The Class (strength grade) of the nut should be the same as or greater than that of the mating screw or bolt. Nuts can be coarse, fine or extra fine thread.



A/F = Across Flats (W)    W = Width    T = Thickness

**ORDER BY ITEM (PACKAGE) NUMBER**

**ISO Coarse Thread**

Product not available in this pack size

ZINC PLATED											
Diameter-Pitch	Approx. Weight (lb) /100 pcs	A/F	T	Clamshell #	Qty	Handy Pak#	Qty	Black Box #	Qty	Bulk Carton #	Qty
M3-.50	0.09	5.5	2.4	—	—	024-203	33	670-003	100	B670-003	12000
M4-.70	0.16	7.0	3.2	—	—	024-204	33	670-004	100	B670-004	10000
M5-.80	0.24	8.0	4.0	—	—	024-205	33	670-005	100	B670-005	15000
M6-1.00	0.47	10.0	5.0	009-250	12	024-206	33	670-006	100	B670-006	9000
M7-1.00	0.62	11.0	5.5	—	—	—	—	670-007	100	—	—
M8-1.25	1.03	13.0	6.5	009-251	10	024-208	18	670-008	100	B670-008	4000
M10-1.50	2.26	17.0	8.0	009-252	6	024-210	11	670-010	100	B670-010	2000
M10-1.50	2.26	17.0	8.0	—	—	—	—	670-011	50	—	—
M12-1.75	3.31	19.0	10.0	009-253	4	024-212	6	670-012	50	B670-012	1200
M14-2.00	4.92	22.0	11.0	—	—	—	—	670-014	25	B670-014	1000
M16-2.00	6.58	24.0	13.0	—	—	—	—	670-016	25	B670-016	600
M18-2.50	9.28	27.0	15.0	—	—	—	—	670-018	25	B670-018	500
M20-2.50	12.00	30.0	16.0	—	—	—	—	670-020	25	B670-020	400
M22-2.50	—	—	—	—	—	—	—	670-022	20	B670-022	200
M24-3.00	20.72	—	—	—	—	—	—	670-024	25	B670-024	200



**ISO Fine Thread**


RED ZINC PLATED											
Diameter-Pitch	Approx. Weight (lb) /100 pcs	A/F	T	Clamshell #	Qty	Handy Pak#	Qty	Black Box #	Qty	Bulk Carton #	Qty
M8-1.00	1.04	13.0	6.5	—	—	024-258	16	670-208	25	B670-208	6000
M8-1.25	1.04	13.0	6.5	—	—	—	—	670-118	100	—	—
M10-1.25	2.00	17.0	8.0	—	—	024-260	12	670-120	50	—	—
M10-1.25	2.30	17.0	8.0	009-165	2	—	—	670-210	25	B670-210	2000
M12-1.50	2.86	19.0	10.0	—	—	240-262	7	670-122	35	—	—
M12-1.50	3.38	19.0	10.0	009-166	2	—	—	670-212	25	B670-212	1700
M14-1.50	4.68	22.0	11.0	—	—	—	—	670-214	25	B670-214	1000
M16-1.50	6.46	24.0	13.0	—	—	—	—	670-216	25	B670-216	800
M18-1.50	8.96	27.0	15.0	—	—	—	—	670-218	25	B670-218	400
M20-1.50	11.66	30.0	16.0	—	—	—	—	670-220	25	B670-220	400

Images do not represent actual size

**670**  
Series

**paulin** METRIC HEX NUTS

PART CLASS #  
800AX | DIN 934= ISO 4032



A/F = Across Flats (W)    W = Width    T = Thickness

ORDER BY ITEM (PACKAGE) NUMBER

ISO Extra Fine Thread

Product not available in this pack size

**GREEN ZINC PLATED**

Diameter-Pitch	Approx. Weight (lb) /100 pcs	A/F	T	Clamshell #	Qty	Handy Pak#	Qty	Black Box #	Qty	Bulk Carton #	Qty
M10-1.00	2.28	17.0	8.0	—	—	<b>024-270</b>	10	<b>670-750</b>	25	—	—
M10-1.00	2.28	17.0	8.0	—	—	—	—	<b>670-755</b>	50	—	—
M12-1.25	3.42	19.0	10.0	<b>009-167</b>	2	<b>024-272</b>	7	<b>670-765</b>	25	—	—

**671**  
Series

**paulin** METRIC HEX NUTS

PART CLASS #  
800AY | DIN 934



ISO Coarse Thread


**BARE METAL**

Diameter-Pitch	Approx. Weight (lb) /100 pcs	A/F	T	Clamshell #	Qty	Handy Pak#	Qty	Black Box #	Qty	Bulk Carton #	Qty
M6-1.00	0.49	10.0	5.0	—	—	—	—	<b>671-006</b>	100	<b>B671-006</b>	9000
M8-1.25	1.02	13.0	6.5	—	—	—	—	<b>671-008</b>	100	<b>B671-008</b>	4000
M10-1.50	2.31	17.0	8.0	—	—	—	—	<b>671-010</b>	100	<b>B671-010</b>	2000
M12-1.75	3.36	19.0	10.0	<b>009-027</b>	12	—	—	<b>671-012</b>	50	<b>B671-012</b>	1200
M14-2.00	4.92	22.0	11.0	—	—	—	—	<b>671-014</b>	25	—	—
M16-2.00	6.50	24.0	13.0	<b>009-028</b>	10	—	—	<b>671-016</b>	25	<b>B671-016</b>	600
M18-2.50	—	27.0	15.0	—	—	—	—	<b>671-018</b>	25	—	—
M20-2.50	12.02	30.0	16.0	<b>009-029</b>	6	—	—	<b>671-020</b>	25	<b>B671-020</b>	400
M24-3.00	20.50	36.0	19.0	<b>009-030</b>	4	—	—	<b>671-024</b>	25	<b>B671-024</b>	200

**672**  
Series

# naulin<sup>®</sup> METRIC CONELOCK<sup>®</sup> LOCK NUTS

PART CLASS #  
800AD




CONELOCK<sup>®</sup> LOCK NUTS are a type of prevailing-torque locknut or self-locking nut. They are frictionally resistant to rotation due to localized precision deformation of the thread in the cone section on top of the nut.

**ORDER BY ITEM (PACKAGE) NUMBER**

**ISO Coarse Thread**

Product not available in this pack size

YELLOW ZINC PLATED											
Diameter-Pitch	Approx. Weight (lb) /100 pcs	A/F	T	Clamshell #	Qty	Handy Pak#	Qty	Black Box #	Qty	Bulk Carton #	Qty
M6-1.00	0.50	10.0	5.5	—	—	—	—	<b>672-206</b>	100	—	—
M8-1.25	1.20	13.0	7.5	—	—	—	—	<b>672-208</b>	100	—	—
M10-1.50	2.80	17.0	9.5	—	—	—	—	<b>672-210</b>	100	—	—
M12-1.75	4.00	19.0	11.5	—	—	—	—	<b>672-212</b>	50	—	—
M14-2.00	5.60	22.0	13.0	—	—	—	—	<b>672-214</b>	25	—	—
M16-2.00	7.20	24.0	15.0	—	—	—	—	<b>672-216</b>	25	—	—
M18-2.50	10.20	27.0	17.0	—	—	—	—	<b>672-218</b>	25	—	—
M20-2.50	13.60	30.0	19.0	—	—	—	—	<b>672-220</b>	25	—	—
M24-3.00	24.40	36.0	22.5	—	—	—	—	<b>672-224</b>	25	—	—

700  
Series**paulin** METRIC NYLON INSERT LOCK NUTSPART CLASS #  
800CL | DIN 985

NYLON INSERT LOCK NUTS have a nylon insert. These locknuts are strong enough to use on most machinery and equipment that are prone to vibration and temperature changes. The nylon insert also won't damage the threads on your bolt. These nuts are reusable, but their holding power lessens with each use. Pair them with compatible Class 8.8 metric bolts.

A/F = Across Flats (W)

H = Height

ORDER BY ITEM (PACKAGE) NUMBER

Product not available in this pack size

**ZINC PLATED**

Diameter-Pitch	Approx. Weight (lb) /100 pcs	A/F	H	Clamshell #	Qty	Handy Pak#	Qty	Black Box #	Qty	Bulk Carton #	Qty
M4-0.70	0.19	7	5.0	—	—	<b>024-224</b>	10	<b>700-004</b>	100	<b>B700-004</b>	9000
M5-0.80	0.23	8	5.0	—	—	<b>024-225</b>	9	<b>700-005</b>	100	<b>B700-005</b>	9000
M6-1.00	0.47	10	6.0	—	—	<b>024-226</b>	9	<b>700-006</b>	100	<b>B700-006</b>	8000
M8-1.25	1.10	13	8.0	—	—	<b>024-228</b>	6	<b>700-008</b>	100	<b>B700-008</b>	4000
M10-1.50	2.41	17	10.0	—	—	<b>024-230</b>	5	<b>700-010</b>	100	<b>B700-010</b>	1500
M12-1.75	3.33	19	12.0	—	—	—	—	<b>700-012</b>	50	<b>B700-012</b>	1000
M14-2.00	5.10	21	14.0	—	—	—	—	<b>700-014</b>	25	<b>B700-014</b>	700
M16-2.00	6.40	24	16.0	—	—	—	—	<b>700-016</b>	25	<b>B700-016</b>	400
M18-2.50	10.08	26	18.5	—	—	—	—	<b>700-018</b>	100	<b>B700-018</b>	300
M20-2.50	12.98	28	20.0	—	—	—	—	<b>700-020</b>	25	<b>B700-020</b>	250
M24-3.00	—	30	24.0	—	—	—	—	<b>700-024</b>	20	<b>B700-024</b>	90