

# Electric Heater

## Industrial & Professional



Industrial - 10 to 20 hours per week



Professional - 20 to 40 hours per week



50 weeks per year

## BEE SERIES

### General Features

- Electric heater, adjustable temperature up to 180°F
- Safety cover
- Automatic start & stop control, pipeline compatible
- Comet 3 ceramic plunger pump
- 50' non-marking hose, 3/8" x 6000 psi with twist disconnect couplers
- 100-mesh filter at pump inlet
- Pressure gauge
- 140°F pump thermal protector
- Spray gun with 38" insulated dual wand and soap spray tips
- 3 quick disconnect spray tips, 15°, 25° & 40°
- 1/2" stainless steel coil, 4000 psi capacity
- Soap injection at the coil outlet
- Continuous temperature rise :
  - S3040BEE : 77 °F
  - S3054BEE : 88 °F
- CSA certified



Truck



Industry



Mine



Heavy Equipment



### S3040BEE

(Stationary Industrial)

Use.....	Industrial
Electric motor .....	8.0 HP
Volts .....	600
Phases.....	3
Amperes (motor.....	8.8
rpm .....	1750
Comet Pump... RW, Crankshaft	
Drive.....	Direct
Psi.....	3000
Gpm .....	4.0
Impact Force.....	11.5
Kw consumption.....	48
Nozzle Orifice .....	04.5
Shipping Weight.....	640 lb
Shipping Code .....	Code 5

### S3054BEE


(Stationary Professional)

Use.....	Professional
Electric motor .....	10.0 HP
Volts .....	600
Phases.....	3
Amperes (motor.....	10.2
rpm .....	1450
Comet Pump... RW, Crankshaft	
Drive.....	Belt
Psi.....	3000
Gpm .....	5.4
Impact Force.....	15.6
Kw consumption.....	72
Nozzle Orifice .....	06.5
Shipping Weight.....	660 lb
Shipping Code .....	Code 5

**Accessories**

**Manual hose reel kit**

# HR-10201416, to be installed on wall, capacity of 200' x 3/8" (3' supply hose, 3/8" ball valve at the reel inlet.




(without extra hose)

MS-1020ST

**Accessories**

**Spring rewind hose reel kit**

10' supply hose, 3/8" ball valve at the reel inlet, includes a hose stop & Q-C.



MS-N7162324JST ..... capacity 60 feet 3/8" hose  
MS-N7182526GST ..... capacity 100 feet 3/8" hose

**Accessories**

**Extra hose**

3/8" x 6000 psi hose on twist disconnect couplers, grey, non-marking.



PN00093VS .....50 feet  
PN00094VS .....75 feet  
PN00095VS .....100 feet  
PN00096VS .....150 feet  
PN00097VS .....200 feet

**Accessories**

**Rotating nozzle kit**

with filter, under spring tension, capacity of 5100 psi.



PN00058VS .....S3040BEE, orifice # 04.5  
PN00060VS .....S3054BEE, orifice # 06.5

**Accessories**

**Foamer with integrated tank**

Foamer kit with 2 liter integrated tank. Includes 3 quick-couplers, one for the foamer, one for the wand and one for the gun outlet.



PN00004VS .....\$195.00

**Accessories**

**Rotative flat surface cleaner**

- 21" model on 4 wheels
- Stainless steel drum
- 4000 psi x 8 gpm max, 180°F maximum
- 2 #2502 tips
- 3/8" quick disconnect plug inlet



AU-SC21SS

**Accessories**

**Rail system, see page 73.**

**Accessories**

**Pipeline system, see page 74.**

All operators should read the owner's manual outlining warranty safety and maintenance recommendations before attempting to operate any machine. Please read and pay attention to all safety recommendations contained in the manual and those labeled on the machine.

## HOTBOX SERIES

### General Features

- Maximum pressure: 5000 psi
- Stationary frame, powder coated, electrostatic paint
- Oil-fired burner
- 9.7 gal. - 37 L polyethylene tank with level indicator
- 1/2" upright steel coil, schedule 80, 5-year warranty
- Adjustable temperature by thermostat up to 302°F
- Control box includes thermostat, burner switch and fuse
- 5' supply hose to connect to pressure washer

### Starting

Manual start of burner by a switch, automatic start of ignition from flow switch.



### **HOTBOX-300**

(Mobile or Stationary)

Volts ..... 120  
 Btu/h ..... 300,000  
 Temperature... 3.2 gpm 190°F\*  
 Chimney outlet ..... 7"  
 Shipping Code ..... Code 4

### **HOTBOX-375**

(Mobile or Stationary)

Volts ..... 120  
 Btu/h ..... 375,000  
 Temperature ..... 4 gpm 190°F\*  
 Chimney outlet ..... 8"  
 Shipping Code ..... Code 4

### **HOTBOX-455**

(Mobile or Stationary)

Volts ..... 120  
 Btu/h ..... 455,000  
 Temperature ... 5.4 gpm 188°F\*  
 Chimney outlet ..... 8"  
 Shipping Code ..... Code 4

### **HOTBOX-38012V**

(Mobile or Stationary)

Volts ..... 12  
 Btu/h ..... 380,000  
 Temperature ... 4.4 gpm 185°F\*  
 Chimney outlet ..... 8"  
 Shipping Code ..... Code 4

\* With a cold water supply of 40 °F



### Option

#### Mobile kit

including 4 x 10" inflated wheels  
and handle

# Hot Water Heater - Gas fired burner

## Industrial

  
10 to 20 hours  
per week

  
50 weeks per year



### General Features – Heating Unit

- Natural gas fired burner of 395 000 btu/h (or propane on request)
- Heating capacity of 180°F for 4 gpm and of 160°F for 5.4 gpm
- Automatic start & stop control, pipeline compatible
- Electronic ignition pilot
- Electronic thermostat
- 120 V supply required
- Stainless steel coil wrap
- 3/4" schedule 80 steel coil
- Compatible to a type « B » gas vent
- CSA certified
- 10" draft hood



### **PN00133VS**

(Natural gas)

Use ..... Professional  
 Btu/h ..... 395,000  
 Psi ..... 3000  
 Temperature rise (1 ..... 120°F at 4 gpm  
 Temperature rise (2 ..... 100°F at 5.4 gpm  
 Hose ..... 5 ft  
 Shipping Code ..... Code 4

### **PN00134VS**

(Propane)

Use ..... Professional  
 Btu/h ..... 395,000  
 Psi ..... 3000  
 Temperature rise (1 ..... 120°F at 4 gpm  
 Temperature rise (2 ..... 100°F at 5.4 gpm  
 Hose ..... 5 ft  
 Shipping Code ..... Code 4

#### Option

#### Side wall power exhaust vent

Side wall power exhaust vent, 120 Vac power venter, allows to use a 6" vent, with stainless steel side wall vent hood.



PN00089VS

All operators should read the owner's manual outlining warranty safety and maintenance recommendations before attempting to operate any machine. Please read and pay attention to all safety recommendations contained in the manual and those labeled on the machine.

**We Simplify Your Work!**