

# Gas engine / Cold water

Pressure cleaning equipment



# Cold Water Pressure Washers - Gas Engine

## Commercial



5 to 10 hours  
per week



50 weeks per year

## CAGE SERIES

### General Features

- Heavy duty protective steel cage
- Electrostatic paint
- Honda or Subaru gas engine
- Comet 3 ceramic plunger pump, direct drive
- Pressure regulator
- Soap injection with regulator
- 25' hose, 3/8" x 4000 psi with quick disconnect couplers
- Spray gun with 32" insulated wand in two section with quick disconnect couplers
- 4 Quick disconnect spray tips, rinse:  
15, 25 & 40°, soap: 65°
- Nozzle orifice 03.0



#### Snap brackets on frame

Conveniently holds commercial duty two piece 32" gun and chromed steel wand. Easy to transport with quick connect couplers and components. Soap/chemical injection built into pump.



#### 3/8" rubber hose x 4000 psi

Comes with quick disconnect couplers



#### Nozzle tray integrated into the frame

4 quick connect spray tips designed to tackle every job.



#### Heavy duty roll cage

The design inspired the name. The Cage is easy to transport and offers maximum component protection.

## CAGE2500

(CAGE SERIES - Portable)

Subaru Engine .....	6 HP
Oil Alert Protection .....	Yes
Comet Pump .....	Axial
rpm .....	3450
Psi .....	2700
Gpm .....	2.4
Impact Force .....	6.6 lb
Thermal Protector .....	No
Weight .....	67 lb
Shipping Code .....	Code 1

### Accessories

#### Pump protection kit

Pump protection kit includes a 100-mesh filter and a 140°F pump thermal protector. Not installed.

**CAGE2500**  
PN00042VS

# Accessories

**Accessories**

**Handle and wheel kit**

Handle with two wheels



PN00209

**Accessories**

**Manual portable hose reel**

Manual hose reel mounted on a ball-bearing mechanism. Can be hooked directly on the CAGE2500GX pressure washer. Capacity of 100' with carrying handle.



PN00205

**Accessories**

**3/8" extra hose**

3/8" extra hose, 4000 psi, with quick connect coupler

- AU-H3825QC .....25 feet
- AU-H3835QC .....35 feet
- AU-H3850QC .....50 feet



**Accessories**

**Foamer kit**

Foamer kit with 1 liter integrated tank and twist-coupler.



PN00008VS

**Accessories**

**Rotating nozzle kit**

with quick couplers, under spring tension, nozzle orifice 03.0, capacity of 3650 psi



PN00039VS

**Accessories**

**Linear surface cleaner**

Water Broom with quick couplers 12", 3 nozzles




AU-WB123G ..... 3 nozzles

**Accessories**

**Telescopic boom**

Max. pressure: 4000 psi.



- MS-B00M12F ..... 3 sections de 6'6" to 12'
- MS-B00M18F ..... 3 sections de 6'6" to 18'
- MS-B00M24F4HD ..... 4 sections de 6'6" to 24'

**Accessories**

**Harness**

MS-BOOMBK



**Accessories**

**Gutter cleaner with Q-C**

MS-BOOMGC



**Accessories**

**Drain cleaning kit**

Drain hose, linear gun with quick couplers and drain nozzle. Max. pressure 3000 psi - 212°F.

- PN00149VS ..... 100 feet
- PN00156VS ..... 200 feet



**Accessories**

**Hose reel kit for drain hose**

With quick disconnect, handle and 4 rubber feet.

**Gun & hose not included**

PN00150VS .....Capacity 100' - 4000 psi- 212°F



**Accessories**

**12" Rotative flat surface cleaner**

- Attached to a wand, a telescopic boom or directly to a gun
- 4000 psi x 8 gpm maximum (180°F max)
- 2 #2502 tips
- 1/4" quick disconnect plug inlet

AU-SC12PM



All operators should read the owner's manual outlining warranty safety and maintenance recommendations before attempting to operate any machine. Please read and pay attention to all safety recommendations contained in the manual and those labeled on the machine.

**We Simplify Your Work!**

# Cold Water Pressure Washers - Gas Engine

## Commercial



5 to 10 hours  
per week



50 weeks per year

## JET SERIES

### General Features

- Tubular frame on 10" pneumatic tires
- Electrostatic paint
- Gas engine with manual start
- Comet 3 ceramic piston direct drive axial pump
- Soap injection
- 25' hose, 3/8" x 4000 psi with quick disconnect couplers
- Spray gun with 36" insulated wand with quick disconnect couplers
- 4 Quick disconnect spray tips, rinse: 15, 25 & 40°, soap: 65°
- Pressure regulator



## JET2500

(JET Series - Mobile)

Subaru Engine .....	6 HP
Oil Alert Protection .....	Yes
Comet Pump .....	Axial
rpm .....	3450
Psi .....	2500
Gpm .....	2.7
Impact Force.....	7.1 lb
Thermal Protector .....	No
Nozzle Orifice .....	03.5
Weight .....	86 lb
Shipping Code .....	Code 1

### Accessories

#### Pump protection kit

Pump protection kit includes a 100-mesh filter and a 140°F pump thermal protector. Not installed.

PN00042VS

### Accessories

#### Rotating nozzle kit

Rotating nozzle kit with quick couplers, under spring tension. Capacity of 3650 psi.



PN00040VS

### Accessories

#### 3/8" extra hose

3/8" extra hose, 4000 psi, with quick connect coupler



AU-H3825QC .....25 feet  
 AU-H3835QC .....35 feet  
 AU-H3850QC .....50 feet

### Accessories

#### Foamer kit

Foamer kit with 1 liter integrated tank. Includes 3 quick-couplers, one for the foamer, one for the wand and one for the gun outlet.



PN00009VS

# Cold Water Pressure Washers - Gas Engine

## Commercial



5 to 10 hours  
per week




50 weeks per year

## JET SERIES

### General Features

- Tubular frame on 12" flat free wheels with dual ball bearings
- Electrostatic paint
- Gas engine with manual start
- Engine installed on anti-vibration subframe with rubber mounts
- Comet direct drive crankshaft pump with 3 ceramic plungers
- Soap injection
- 3/8" x 4000 psi hose with quick disconnect couplers
- Spray gun with 36" insulated wand with quick disconnect couplers
- 4 Quick disconnect spray tips, rinse: 15, 25 & 40°, soap: 65°
- Pressure regulator



External by-pass system to a tank on JET3500-BP & JET4000-BP



### Accessories

#### Pump protection kit

Pump protection kit includes a 100-mesh filter and a 140 °F pump thermal protector. Not installed.

PN00042VS ... JET2700S  
PN00044VS ... JET2700GX, JET3500,  
JET3500-BP & JET4000-BP

**New**

### JET2700S

(JET Series - Mobile)

Subaru Engine ..... 6 HP  
Oil Alert Protection ..... Yes  
Comet Pump ..... Axial  
rpm ..... 3450  
Psi ..... 2700  
Gpm ..... 2.4  
Impact Force ..... 6.6 lb  
Thermal Protector ..... No  
Hose ..... 25 ft  
Nozzle Orifice ..... 03.0  
Weight ..... 93 lb  
Shipping Code ..... Code 1  
**CODE.....PN00241**

### JET2700GX

(JET Series- Mobile)

Honda Engine ..... 6.5 HP  
Oil Alert Protection ..... Yes  
Comet Pump ..... Crankshaft  
rpm ..... 3450  
Psi ..... 2700  
Gpm ..... 2.5  
Impact Force ..... 6.8 lb  
Thermal Protector ..... Yes  
Hose ..... 25 ft  
Nozzle Orifice ..... 03.0  
Weight ..... 109 lb  
Shipping Code ..... Code 1  
**CODE.....PN00242**

### JET3500 /JET3500-BP

(JET Series - Mobile)

Honda Engine ..... 13 HP  
Oil Alert Protection ..... Yes  
Comet Pump ..... Crankshaft  
rpm ..... 3450  
Psi ..... 3500  
Gpm ..... 4.0  
Impact Force ..... 12.4 lb  
Thermal Protector ..... Yes  
Hose ..... 50 ft  
Nozzle Orifice ..... 04.0  
Weight ..... 155 lb  
Shipping Code ..... Code 1  
**CODE (JET3500) .....PN00243**  
**CODE (JET3500-BP).....PN00244**

### JET4000-BP

(JET Series - Mobile)

Vanguard Engine ..... 14 HP  
Oil Alert Protection ..... Yes  
Comet Pump ..... Crankshaft  
rpm ..... 3450  
Psi ..... 4000  
Gpm ..... 4.0  
Impact Force ..... 13.3 lb  
Thermal Protector ..... Yes  
Hose ..... 50 ft  
Nozzle Orifice ..... 04.0  
Weight ..... 158 lb  
Shipping Code ..... Code 1  
**CODE.....PN00245**

# Accessories



## Accessories

### Rotating nozzle kit, capacity of 3650 psi

with quick couplers, under spring tension.



PN00039VS ...JET2500, JET2500GX & JET2700GX, orifice 03.0  
PN00006VS .....JET3500 & JET3500-BP, orifice 04.0

## Accessories

### Rotating nozzle kit, capacity of 5100 psi

with quick couplers, under spring tension.



PN00027VS .....JET4000-BP, orifice 04.0

## Accessories

### Manual hose reel kit

capacity of 4000 psi. Includes : manual hose reel, quick couplers, reel bracket, nuts. Hose not included. Add this hose reel to your extra hose length.



MS-ENRJET5 .....Capacity of 100' hose x 3/8"  
MS-ENRJET6 .....Capacity of 200' hose x 3/8"

## Accessories

### 3/8" extra hose

3/8" x 4000 psi extra hose with quick connect couplers

AU-H3835QC .....35 feet  
AU-H3850QC .....50 feet  
AU-H3875QC .....75 feet  
AU-H38100QC .....100 feet  
AU-H38150QC .....150 feet  
AU-H38200QC .....200 feet



## Accessories

### Foamer kit

Foamer kit with 1 liter integrated tank. Includes 3 quick-couplers, one for the foamer, one for the wand and one for the gun outlet.



PN00009VS ..... For all models

## Accessories

### Foamer kit

Foamer kit with 2 liter integrated tank. Includes 3 quick-couplers, one for the foamer, one for the wand and one for the gun outlet.



PN00004VS .....For JET3500, JET3500-BP & JET4000-BP

## Accessories

### Telescopic boom

Max. pressure: 4000 psi.



MS-BOOM12F ..... 3 sections de 6'6" to 12'  
MS-BOOM18F ..... 3 sections de 6'6" to 18'  
MS-BOOM24F4HD ..... 4 sections de 6'6" to 24'

## Accessories

### Harness

MS-BOOMBK



## Accessories

### Gutter cleaner with Q-C

MS-BOOMGC



## Accessories

### Drain cleaning kit

Drain hose, linear gun with quick couplers and drain nozzle.

Max. pressure 3000 psi - 212 °F.



PN00149VS ..... 100 feet  
PN00156VS ..... 200 feet

## Accessories

### Hose reel kit for drain hose

With quick disconnect, handle and 4 rubber feet



#### Gun & hose not included

PN00150VS .....Capacity 100' - 4000 psi - 225°F  
PN00151VS .....Capacity 200' - 4000 psi - 400°F

## Accessories

### Linear surface cleaner

Water Broom with quick coupler

12", 3 nozzles.

16", 4 nozzles.

AU-WB123G ..... 3 nozzles  
AU-WB164G ..... 4 nozzles



## Accessories

### 16" rotative flat surface cleaner

- Nylon brush
- Polyethylene drum
- 4000 psi x 8 gpm maximum (180°F max)
- 2 #25025 tips
- 3/8" quick disconnect plug inlet

AU-SC16NB



All operators should read the owner's manual outlining warranty safety and maintenance recommendations before attempting to operate any machine. Please read and pay attention to all safety recommendations contained in the manual and those labeled on the machine.

**We Simplify Your Work!**

# Cold Water Pressure Washers - Gas Engine

## Professional



20 to 40 hours  
per week



50 weeks per year

## LP SERIES



### General Features

- Frame with protection cage, 16" tires
- Electrostatic paint
- Gas engine with oil alert
- Comet belt drive crankshft pumpwith 3 ceramic plungers
- Pressure regulator
- 50' hose, 3/8" x 6000 psi with quick disconnect couplers
- Spray gun with insulated wand
- 100-mesh filter at pump inlet
- Pressure gauge
- 140°F pump thermal protector
- 3 quick disconnect spray tips, rinse: 15, 25 & 40°. Extra 65° soap nozzle on LP3545G & LP4053GC models only.



### Accessories

#### Soap injection kit

Soap injection kit low pressure includes a 4 liter soap jar, injector and soap nozzle, for LP5050G. Not installed.

PN00036

### LP3545G

(AS Series - Mobile)

Honda Engine .....	GX390
Elect.start .....	No
Oil Alert Protection .....	Yes
rpm .....	1150
Psi .....	3500
Gpm .....	4.3
Impact Force.....	13.4 lb
Wand.....	36"
Soap Injection... Yes with nozzle	
Nozzle Orifice .....	04.5
Weight.....	228 lb
Shipping Code .....	Code 5

### LP4053GC

(LP Series - Mobile)

Honda Engine .....	GX630
Elect.start .....	Yes
Oil Alert Protection .....	Yes
rpm .....	1550
Psi .....	4000
Gpm .....	5.3
Impact Force.....	17.6 lb
Wand.....	48"
Soap Injection... Yes with nozzle	
Nozzle Orifice .....	05.0
Weight.....	255 lb
Shipping Code .....	Code 5

### LP5050G

(LP Series - Mobile)

Honda Engine .....	GX630
Elect.start .....	Yes
Oil Alert Protection .....	Yes
rpm .....	1650
Psi .....	5000
Gpm .....	5.0
Impact Force.....	18.6 lb
Wand.....	48"
Soap Injection.....	No
Nozzle Orifice .....	04.5
Weight.....	320 lb
Shipping Code .....	Code 5

### LP3080G

(LP Series - Mobile)

Honda Engine .....	GX630
Elect.start .....	Yes
Oil Alert Protection .....	Yes
rpm .....	1550
Psi .....	3000
Gpm .....	8.0
Impact Force.....	23 lb
Wand.....	48"
Soap Injection.....	No
Nozzle Orifice .....	09.0
Weight.....	330 lb
Shipping Code .....	Code 5

**Accessories**

**Rotating nozzle kit**

with quick couplers, under spring tension, capacity of 5100 psi.



- PN00019VS .....LP3545G & LP5050G, orifice 04.5
- PN00033VS .....LP4053GC, orifice 05.0
- PN00033VS .....LP4053GC, orifice 08.0

**Accessories**

**Foamer kit**

Foamer kit with 2 liter integrated tank. Includes 3 quick-couplers, one for the foamer, one for the wand and one for the gun outlet.



- PN0004VS .....LP3545G et LP4053GC

**Accessories**

**Manual hose reel kit**

capacity of 200' x 38 ". Includes : manual hose reel, quick couplers, reel bracket, nuts, pump protective shield (installed by the dealer) Hose not included. Add this hose reel to your extra hose length. Standard hose can not be replaced or changed at the factory.

- MS-LPCENR10H ....LP3545G, LP4053GC & LP3080G
- MS-LPCENR15H ....LP5050G

**Accessories**

**3/8" extra hose**

3/8" extra hose on Q-C, 6000 psi, grey, Non-marking.



- PN00104VS .....50 feet
- PN00105VS .....75 feet
- PN00029VS .....100 feet
- PN00030VS .....150 feet
- PN00031VS .....200 feet

**Accessories**

**Telescopic boom**

Quick couplers  
Max. pressure: 4000 psi.  
(Not available with LP5050G)



- MS-B00M12F ..... 3 sections of 6'6" to 12'
- MS-B00M18F ..... 3 sections of 6'6" to 18'
- MS-B00M24F4HD ..... 4 sections of 6'6" to 24'

**Accessories**

**Harness**

- MS-B00MBK



**Accessories**

**Gutter cleaner with Q-C**

- MS-B00MGC



**Accessories**

**Sandblasting kit**

15' of suction hose for sand with quick couplers.  
Pressure capacity: 1500 to 5500 psi



- PN00035VS

**Accessories**

**15 gallon mobile tank for sandblast**

15 gallon cone bottom tank with metering valves for air and sand with quick-couplers.



- MS-SB15G

All operators should read the owner's manual outlining warranty safety and maintenance recommendations before attempting to operate any machine. Please read and pay attention to all safety recommendations contained in the manual and those labeled on the machine.

**We Simplify Your Work!**