


PTO PUMPS

- SLIPS ONTO TRACTOR PTO SHAFT (NO GEARBOX REQUIRED)
- 2000 PSI MAXIMUM PRESSURE
- BARBED ADAPTOR FOR HOSE INCLUDED
- FEMALE PIPE ADAPTOR FOR 3/4 NPT INCLUDED


PART NUMBER	HP @ 2000 PSI	2000 PSI		INLET	OUTLET	SHAFT	DIM E	
		RPM	GPM					
HC-PTO-1A	32	540	21	SAE 16	SAE 12	1 3/8 - 6 T	6.35"	
HC-PTO-9A	27		17				5.97"	
HC-PTO-2A	18		11				5.60"	
HC-PTO-7A	12		7				5.23"	
HC-PTO-3A	34	1000	22.5				1 3/8 - 21 T	5.60"
HC-PTO-8A	27		13.5					5.23"



GEAR BOX / PUMP ASSEMBLY

- SLIPS ONTO 540 RPM TRACTOR PTO SHAFTS
- ADAPTS TO 1 3/8 - 6T SPLINE SHAFT
- OTHER PUMPS FLOW AVAILABLE UPON REQUEST

PART NUMBER	HP @ 2000 PSI	GPM	MAX PSI	INLET	OUTLET
2.5PB-PTO-38D	25.4	19.2	2500	SAE 16	SAE 12
2.5PB-PTO-32D	21.4	16.3	3300		
2.5PB-PTO-22D	14.7	11	3600		



2 STAGE PUMPS

- IDEAL FOR LOGSPLITTERS
- CLOCKWISE ROTATION
- 3600 RPM MAX SPEED
- UNLOAD PRESSURE SET TO 650 PSI (400-900 PSI RANGE)
- 1" TUBE INLET

PART NO	GPM @ 3600 RPM		SHAFT	MOUNTING FLANGE	OUTLET PORT
	HIGH SPEED LOW PRESSURE	LOW SPEED HIGH PRESSURE			
CBN-8.8/3.0	11	2.8	1/2 KEYED	SAE AA - 4 BOLT	1/2 NPT
CBN-13/4.2	16	4			
CBDN-16/7	22	6	5/8 KEYED	SAE A - 2 BOLT	3/4 NPT
CBDN-22/7	28	6			



HAND PUMPS - WHP TYPE

- 3500 PSI MAXIMUM PRESSURE
- "SA" SERIES IS SINGLE ACTING
- "DA" SERIES HAVE A BUILT IN DIRECTIONAL CONTROL VALVE
- 2.1 CUBIC INCH PER CYCLE (ONE UP AND ONE DOWN)

PART NUMBER	DESCRIPTION
WHP-21-DA	2.1 CUBIC INCH DOUBLE ACTING HEAD
WHP-21-SA	2.1 CUBIC INCH SINGLE ACTING HEAD
WHP-T-300	STEEL RESERVOIR, 1.3 GALLONS
WHP-T-180	STEEL RESERVOIR, 0.8 GALLON

