

PYROJACKET - FIRE SLEEVE

Item No.	Round Dia. (inch)
FS-04	0.25
FS-05	0.31
FS-06	0.37
FS-07	0.44
FS-08	0.50
FS-10	0.63
FS-12	0.75
FS-14	0.88
FS-16	1.00
FS-18	1.13
FS-20	1.25
FS-22	1.37
FS-24	1.50

Item No.	Round Dia. (inch)
FS-26	1.63
FS-28	1.75
FS-32	2.00
FS-36	2.25
FS-40	2.50
FS-44	2.75
FS-48	3.00
FS-52	3.25
FS-56	3.50
FS-60	3.75
FS-64	4.00
FS-72	4.50
FS-80	5.00



Industrial grade Pyrojacket® Fire Sleeve - QUICK FACTS	
Custom Colors Available on Demand	
Continuous Operating Temperature	500°F (260°C)
Maximum Short Term Exposure	3000°F (1650°C)
Molten Splash Resistance	Outstanding
Flame Resistance	Very Good
Abrasion Resistance	Very Good
Flexibility	Outstanding
Water and Oil Resistance	Outstanding

PYROJACKET - VELCRO FIRE SLEEVE

Item No.	Round Dia. (inch)
FS-10	0.63
FS-12	0.75
FS-14	0.88
FS-16	1.00
FS-18	1.13
FS-20	1.25
FS-22	1.37
FS-24	1.50
FS-26	1.63
FS-28	1.75

Item No.	Round Dia. (inch)
FS-32	2.00
FS-36	2.25
FS-40	2.50
FS-44	2.75
FS-48	3.00
FS-52	3.25
FS-56	3.50
FS-60	3.75
FS-64	4.00



Pyrojacket® Fire Sleeve - QUICK FACTS

Custom Colors Available on Demand

Continuous Operating Temperature	500°F (260°C)
Maximum Short Term Exposure	3000°F (1650°C)
Molten Splash Resistance	Outstanding
Flame Resistance	Very Good
Abrasion Resistance	Very Good
Flexibility	Good
Water and Oil Resistance	Outstanding