



4.5" ANGLE GRINDERS



WARRANTY
LONG-RUN SERVICEGUARD™ Protection Plan
24 MONTHS

MINI GRINDER™

Order no. 30-A 161

Light, compact and durable
The Mini™ 4.5" grinder's state-of-the-art features include the new Walter anti-vibration handle that makes the grinder more comfortable to use and Walter's QUICK-R™ instant release function for disc change outs that take just seconds. The Mini™ has an additional 100 watts of power and features a rear vent to keep the armature cooler, allowing you to work longer while extending the life of the tool.



WARRANTY
LONG-RUN SERVICEGUARD™ Protection Plan
24 MONTHS

MINI PS™

Order no. 30-A 163

Additional job site safety
The Mini PS™ is the ideal choice when a paddle switch is needed on a 4 ½" grinder. It can be plugged into a generator, making it the perfect fit for construction sites. The double action non-locking paddle switch will stop when you release it, making it the safest choice without sacrificing productivity.



WARRANTY
LONG-RUN SERVICEGUARD™ Protection Plan
24 MONTHS

MINI PLUS™

Order no. 30-A 255

Powerful variable speed grinder
The MINI PLUS™ grinder provides premium performance and the most advanced features in the industry. Put it to work taking down welds, cutting tubing, light sanding, or removing rust and paint. With an autobalancer, our DYNAMAX™ speed control and POWERGUARD™ protection from overheating, the MINI PLUS™ delivers superior performance no matter the job. Remove more material faster while also significantly extending the life of your abrasives with a premium power tool.

Description	MINI™	MINI PS™	MINI PLUS™
Model name	6161K	6163B	6255J
Order No.	30-A 161	30-A 163	30-A 255
Anti vibration side handle	√	√	√
Safety clutch	√	√	√
QUICK-R™ instant release function	√	√	√
Tool-free rotating guard	√	√	√
Non-locking paddle switch		√	
Lock-on switch	√		
AC/DC compatibility	√	AC only	AC only
Stabilizer™			√
Soft-Start™			√
Restart protection			√
DYNAMAX™ RPM monitoring			√
POWERGUARD™ overheat protection			√
LED indicator			√
DIALSPEED™ variable RPM selector			√
Spindle	5/8" - 11	5/8" - 11	5/8" - 11
RPM no-load	10,500	10,500	2,800 to 10,500
Amps	8.5 A	8.5 A	9.5 A
Power	900 W	900 W	1000 W
Tool weight	4.6 lbs	4.6 lbs	4.8 lbs
Maximum wheel diameter	4 ½"	4 ½"	5"
Standard equipment			
Wheel guard type 27	48-M 558	48-M 558	48-M 444
Side handle	30-B 075	30-B 075	30-B 075
Inner flange	30-B 057	30-B 057	30-B 057
QUICK-R™ front nut	30-B 020	30-B 020	30-B 020
Optional equipment			
Close guard adaptor	34-B 010	34-B 010	34-B 011
Manual clamping nut	30-B 037	30-B 037	30-B 037
Pin key wrench	48-Z 148	48-Z 148	48-Z 148
SPIN-ON™ kit	30-B 024	30-B 024	30-B 024

5" ANGLE GRINDERS



SUPER 5™

Order no. 30-A 150

The perfect intermediate size grinder

Now boasting a 10.5A motor, this grinder is the right choice for those jobs that require extra power from a lightweight tool. This industrial grade power tool is built to last, and when paired with 5" Walter abrasives it provides one of the safest and most productive systems to tackle a wide range of jobs.



SUPER 5 PS™

Order no. 30-A 153

Safety and performance

The Super 5 PS™ allows you to grind, cut, sand, finish and clean at a much faster and smoother rate. Furthermore, rest assured that when you hold the Super 5 PS™, you are holding the safest grinder thanks to Soft Start™, Powerguard™, a safety clutch and a safety restart that prevents the tool from starting on its own after a power interruption. The Super 5 PS also comes with a paddle switch and a mechanical brake which stops the grinder within 2 seconds of relieving the trigger.



PRO 5™

Order no. 30-A 157

The best ratio of weight and performance

The Pro 5™ has no peers among 5" angle grinders when it comes to removal rate or cutting speed. Equipped with the Walter Stabilizer™, DYNAMAX™, Powerguard™, and Soft Start™ technologies, the Pro 5™ is in a class of its own and offers the most comprehensive safety and productivity enhancing features.

Description	SUPER 5™	SUPER 5 PS™	PRO 5™
Model name	6150i	6153C	6157A
Order No.	30-A 150	30-A 153	30-A 157
Anti vibration side handle	√	√	√
Safety clutch	√	√	√
QUICK-R™ instant release function	√	√	√
Tool-free rotating guard	√	√	√
Non-locking paddle switch		√	
Mechanical brake system		2-second brake	
Lock-on switch	√		√
AC/DC compatibility	√	AC only	AC compatibility only
Stabilizer™			√
Soft-Start™		√	√
Restart protection		√	√
DYNAMAX™ RPM monitoring		√	√
POWERGUARD™ overheat protection		√	√
LED indicator		√	√
Spindle	5/8" - 11	5/8" - 11	5/8" - 11
RPM no-load	11,000	11,000	11,000
Amps	10.5 A	13.5 A	13.5 A
Power	1200 W	1550 W	1550 W
Tool weight	5.3 lbs	5.5 lbs	5.7 lbs
Maximum wheel diameter	5"	5"	5"
Standard equipment			
Wheel guard type 27	48-M 444	48-M 444	48-M 444
Side handle	30-B 075	30-B 075	30-B 075
Inner flange	30-B 057	30-B 057	30-B 057
QUICK-R™ front nut	30-B 020	30-B 020	30-B 020
Optional equipment			
Close guard adaptor	34-B 011	34-B 011	34-B 011
Manual clamping nut	30-B 037	30-B 037	30-B 037
Pin key wrench	48-Z 148	48-Z 148	48-Z 148
SPIN-ON™ kit	30-B 024	30-B 024	30-B 024

6" ANGLE GRINDERS



WARRANTY
LONG-RUN SERVICEGUARD™ Protection Plan **24** MONTHS

BIG 6™

Order no. 30-A 260

The best ratio of weight and performance

The Big 6™ is the most powerful grinder in its class. The only grinder that can deliver 1,700 watts with a 6" wheel capacity, the Big 6™ is built for heavy duty applications. It offers a secure grip thanks to the new Walter Stabilizer™ system, which reduces vibration and increases the life of each wheel by at least 30%. The Big 6™ has extensive safety features, making it ideal for production environments that require the performance of a 7" or even 9" grinder without the weight that contributes to operator fatigue.



WARRANTY
LONG-RUN SERVICEGUARD™ Protection Plan **24** MONTHS

BIG 6 PS™

Order no. 30-A 263

Heavy-duty performance with additional safety features

The Big 6 PS™ comes with a paddle switch and a mechanical brake to stop the grinder within 2 seconds of relieving the trigger. The Big 6 PS™ is the safest heavy duty grinder on the market and also comes with a Walter Stabilizer™ to reduce vibration, improving workplace ergonomics while improving the life and removal rate of your abrasives.

Description	BIG 6™	BIG 6 PS™
Model name	6260J	6263B
Order No.	30-A 260	30-A 263
Anti vibration side handle	✓	✓
Safety clutch	✓	✓
QUICK-R™ instant release function	✓	✓
Tool-free rotating guard	✓	✓
Lock-on switch	✓	
Non-locking paddle switch		✓
Mechanical brake system		✓
AC/DC compatibility	AC compatibility only	AC compatibility only
Stabilizer™	✓	✓
Soft-Start™	✓	✓
Restart protection	✓	✓
DYNAMAX™ RPM monitoring	✓	✓
POWERGUARD™ overheat protection	✓	✓
LED indicator	✓	✓
Spindle	5/8" - 11	5/8" - 11
RPM no-load	9,600	9,600
Amps	14.5 A	14.5 A
Power	1700 W	1700 W
Tool weight	5.9 lbs	6.2 lbs
Maximum wheel diameter	6"	6"
Standard equipment		
Wheel guard type 27	48-M 446	48-M 446
Side handle	30-B 075	30-B 075
Inner flange	30-B 057	30-B 057
QUICK-R™ front nut	30-B 020	30-B 020
Optional equipment		
Close guard adaptor	34-B 011	34-B 011
Manual clamping nut	30-B 037	30-B 037
Pin key wrench	48-Z 148	48-Z 148
SPIN-ON™ kit	30-B 024	30-B 024

IRONMAN™ GRINDERS

WARRANTY

LONG-RUN
SERVICEGUARD™
Protection Plan

24
MONTHS



IRONMAN™

Order no. 30-A 560

Top performance in strenuous and prolonged applications

With its ergonomic rat-tail design, the Ironman™ delivers 1,750 watts with 6" wheel capacity. It comes with a Walter Stabilizer™ to reduce vibration and extend the life and removal rate of your abrasives by up to 30%. Ideal for prolonged applications, when combined with Walter abrasives, Ironman™ is among the industry's most productive systems available.

IRONMAN™ PS

Order no. 30-A 563

Exceptional performance with added safety features

If it's high performance and added safety you're after, the Ironman™ PS comes with a paddle switch and a mechanical brake to stop grinding wheels from turning within 2 seconds of relieving the trigger, and cutting wheels within 1.5 seconds. It delivers 1,750 watts of power and comes with a Walter Stabilizer™ to reduce vibration, improve ergonomics and extend the life and removal rate of your abrasives.

Description	IRONMAN™	IRONMAN™ PS
Model name	6560A	6563A
Order No.	30-A 560	30-A 563
Anti vibration side handle	√	√
Safety clutch	√	√
QUICK-R™ instant release function	√	√
Tool-free rotating guard	√	√
Lock-on switch	√	
Mechanical brake system		2-second brake
AC/DC compatibility	AC compatibility only	AC compatibility only
Stabilizer™	√	√
Soft-Start™	√	√
Restart protection	√	√
DYNAMAX™ RPM monitoring	√	√
LED indicator	√	√
Spindle	5/8" - 11	5/8" - 11
RPM no-load	9,600	9,600
Amps	14.5 A	14.5 A
Power	1750 W	1750 W
Tool weight	6.2 lbs	6.2 lbs
Maximum wheel diameter	6"	6"
Standard equipment		
Wheel guard type 27	48-M 444 / 48-M 446	48-M 444 / 48-M 446
Side handle	30-B 075	30-B 075
QUICK-R™ front nut	30-B 020	30-B 020
Optional equipment		
Close guard adaptor	34-B 011	34-B 012
Manual clamping nut	30-B 037	30-B 037
Pin key wrench	48-Z 148	48-Z 148
SPIN-ON™ kit	30-B 024	30-B 024

MAXI™ GRINDERS



MAXI™ 7"
Order no. 30-A 170

MAXI™ 9"
Order no. 30-A 190

Pound for pound, they deliver more power and better performance

These full-size industrial angle grinders now deliver even more power and speed to get heavy-duty grinding and finishing jobs done faster and with less effort. Well established and recognized quality motors generate less heat and deliver a higher removal rate under load. These grinders will stay on the job longer in the most demanding applications such as bevelling, grinding and taking down heavy welds.

WARRANTY

LONG-RUN
SERVICEGUARD™
Protection Plan

24
MONTHS

Description	MAXI™ 7"	MAXI™ 9"
Model name	6170i	6190i
Order No.	30-A 170	30-A 190
Anti vibration side handle	√	√
Lock-on switch	√	√
AC/DC compatibility	√	√
Swivel rear handle	√	√
Spindle	5/8" - 11	5/8" - 11
RPM no-load	8,500	6,800
Amps	15 A	15 A
Power	2400 W	2400 W
Tool weight	12.8 lbs	12.8 lbs
Maximum wheel diameter	7"	9"
Standard equipment		
Wheel guard	48-M 516	48-M 517
Side handle	48-M 401	48-M 401
Inner flange	30-B 057	30-B 057
Clamping nut	30-B 037	30-B 037
Pin key wrench	48-M 483	48-M 483
Optional equipment		
Cut-off guard	34-B 065	34-B 066

* Non-locking switch available upon request for MAXI™ grinder models.

STRAIGHT-MATE™

Order no. 30-A 606 (30A607 for the kit)

The ultimate straight grinder and lightweight polishing and buffing tool

The Straight-Mate™ packs a punch as the ultimate lightweight straight grinder with Walter's Dynamax™ variable speed control and RPM range of 1,600 to 4,800. A versatile grinding, polishing and buffing tool.



Features

- ▷ *Dynamax™ variable speed control*
- ▷ *RPM range: 1,600-4,800*
- ▷ *Lightweight: 7 lbs (3.2 kg)*
- ▷ *Max wheel diameter: 6" (150mm).*
- ▷ *Compatible with cotton wheels and polishing pastes*
- ▷ *Compatible with wire brush and Line-Mate™ drums*
- ▷ *Compatible with non-woven abrasives,*
- ▷ *Plugs and cones*
- ▷ *Compatible with snagging wheels*

STRAIGHT-MATE KIT

Order no. 30-A 607

Includes:

- 1 FX Stainless (07-X 661)
- 1 Blendex U (07-U 613)
- 1 2-in-1 Turbo Drum (07-K 441)
- 1 2-in-1 Drum (07-K 342)
- 1 Blendex Drum (07-M 323)
- 1 Cotton Drum (07-T 425)
- 1 Polishing Paste (07-T 907)
- 1 Wire Drums (13-M 454)
- 1 Straight-Mate (30-A 606)

Description	STRAIGHT-MATE™
Model Name	6606A
Order No.	30-A 606 (30A607 for kit)
AC compatibility only	√
Soft-Start ^{MC}	√
Restart protection	
DYNAMAX™ RPM monitoring	√
LED indicator	
DIALSPEED™ variable RPM selector	√
Spindle	5/8"-11
RPM no-load	1600-4800
Amperage	11.8
Power	1300W
Tool weight	7 lbs
Maximum wheel diameter	6" (150mm)

SANDER-POLISHER

QUICK-STEP FINISHER™

Order no. 30-A 275

The perfect tool for surface finishing and polishing

This variable speed tool was specifically designed to get the most out of the QUICK-STEP™ surface finishing system. Whether you sand, buff or polish, the QUICK-STEP Finisher™ will provide you with a uniform, top quality finish and reduced finishing times. With all the latest electronic safety controls, the QUICK-STEP Finisher™ is the smart choice for professionals looking to reduce cycle time and finishing costs.



QUICK-STEP Finisher™ system

Order no. 30-A 277

Includes:

- 1 Quick-Step interface pad (07-Q 045)
- 1 Quick-Step backing pad MG (07-Q 149)
- 1 Quick-Step FLEX grit 60 (07-Q 506)
- 1 Quick-Step FLEX grit 120 (07-Q 512)
- 2 Quick-Step Blendex med (07-R 453)
- 1 Quick-Step Blendex fine (07-R 454)
- 1 Quick-Step FX (07-X 845)
- 4 Quick-Step XX (15-V 418)
- 1 Quick-Step Finisher (30-A 275) with standard equipment plus carrying case



Description	QUICK-STEP FINISHER™
Model name	6275B
Order No.	30-A 275
Anti vibration side handle	✓
Safety clutch	✓
QUICK-R™ instant release function	✓
Lock-on switch	✓
AC/DC compatibility	AC compatibility only
Soft-Start™	✓
Restart protection	✓
DYNAMAX™ RPM monitoring	✓
POWERGUARD™ overheat protection	✓
LED indicator	✓
DIALSPEED™ variable RPM selector	✓
Spindle	5/8" - 11
RPM no-load	2,000 to 7,600
Amps	12.2 A
Power	1550 W
Tool weight	5.5 lbs
Maximum wheel diameter	6"
Standard equipment	
Wheel guard type 27	48-M 446
Side handle	30-B 075
Inner flange	30-B 057
QUICK-R™ front nut	30-B 020
Optional equipment	
Manual clamping nut	30-B 037
Pin key wrench	48-Z 148

SANDER-POLISHER

QUICK-STEP BIG-BUFF III™

Order no. 30-A 265

The most comfortable and versatile tool for metal polishing

The Quick-Step Big-Buff III™ is a variable speed tool designed to provide operators with the power and versatility to tackle any job that requires sanding, buffing or polishing. The ergonomic design reduces operator fatigue and ensures smooth operation during the most demanding jobs.



QUICK-STEP BIG-BUFF III™ SYSTEM – 4 1/2"

Order no. 30-A 267

Includes:

- 1 Quick-Step interface pad (07-Q 045)
- 1 Quick-Step backing pad MG (07-Q 149)
- 1 Quick-Step FLEX grit 60 (07-Q 506)
- 1 Quick-Step FLEX grit 120 (07-Q 512)
- 2 Quick-Step Blendex med (07-R 453)
- 2 Quick-Step Blendex fine (07-R 454)
- 1 Quick-Step Felt (07-T 450)
- 1 Quick-Step high polish (07-T 454)
- 1 instant polishing paste (07-T 907)
- 1 BLENDEX U™ Cup Disc (07-U 451)
- 1 Quick-Step FX (07-X 845)
- 1 ENDURO-FLEX 2-in-1™ (15-I 453)
- 2 Quick-Step XX (15-V 418)
- 1 Quick-Step Big-Buff and carrying case (30-A 265)



Description	QUICK-STEP BIG-BUFF III™
Model name	6265C
Order No.	30-A 265
Lock-on switch	√
AC/DC compatibility	AC compatibility only
Soft-Start™	√
DYNAMAX™ RPM monitoring	√
POWERGUARD™ overheat protection	√
DIALSPEED™ variable RPM selector	√
Spindle	5/8" - 11
RPM no-load	2,000 to 7,300
Amps	12.4 A
Power	1500 W
Weight	6 lbs
Maximum wheel diameter	6"
Standard equipment	
Side handle	30-B 075
Inner flange	30-B 057
Manual clamping nut	30-B 037
Pin key wrench	48-Z 148

FILLET WELD GRINDER

ULTI-MATE™

Variable speed fillet weld grinder

Ulti-Mate™ is a variable speed fillet weld grinder and finishing tool designed to work in tight corners that other tools have a difficult time reaching. By combining this tool and our range of quality abrasives, you can go from a rough weld all the way to a mirror finish in just minutes.



ULTI-MATE™ FILLET WELD GRINDER SYSTEM

Order no. 30-A 287

Includes:

- 1 Ulti-Mate grinder
- 1 Enduro-Flex 2-in-1 Turbo (15-I 451)
- 1 Enduro-Flex 2-in-1 (15-I 453)
- 1 Blendex U Turbo, ¼" width (07-U 625)
- 1 Blendex U Turbo, ⅛" width (07-U 615)
- 1 Blendex U 2SF, ¼" width (07-U 621)
- 1 FX Stainless wheel, ¼" width (07-X 662)



Description	ULTI-MATE™ WELD GRINDER SYSTEM
Model name	6285A
Order No.	30-A 287
Anti vibration side handle	✓
Safety clutch	✓
Lock-on switch	✓
AC/DC compatibility	AC compatibility only
Soft-Start™	✓
Restart protection	✓
DYNAMAX™ RPM monitoring	✓
POWERGUARD™ overheat protection	✓
LED indicator	✓
DIALSPEED™ variable RPM selector	✓
Spindle	5/8" - 11
RPM no-load	2,500 to 8,750
Amps	12.2 A
Power	1550 W
Weight	7.7 lbs
Maximum wheel diameter	6"

TUBE / PIPE SANDER

RAIL-MATE™

Remove welds and finish pipes, tubes and railings faster

This power tool allows you to use our premium abrasive products to finish pipes, tubes and railings. This powerful finishing tool features Soft-Start technology to avoid kickback when starting the tool, Dialspeed™ variable speed control and Dynamax™ RPM Monitoring to maintain consistent speed under load.



RAIL-MATE™ SANDER SYSTEM

Order no. 30-A 289

Includes:

- 1 Rail-Mate sander
- 6 Coolcut XX belts (2 of each: grit 60, 14-X 156; grit 80, 14-X 158; grit 120: 14-X 162)
- 3 Blendex belts (1 of each grade: Coarse, 07-D 152; Medium 07-D 153; Fine 07-D 154)



Description	RAIL-MATE™ SANDER SYSTEM
Model name	6288A
Order No.	30-A 289
Lock-on switch	√
AC/DC compatibility	AC compatibility only
Soft-Start™	√
Restart protection	√
DYNAMAX™ RPM monitoring	√
POWERGUARD™ overheat protection	√
LED indicator	√
DIALSPEED™ variable RPM selector	√
Spindle	5/8" - 11
RPM no-load	1,600 to 3,200
Surface speed	3-12 m/sec.
MAX belt size L x W	760 mm x 40 mm
MAX pipe diameter	7 in. (180 mm)
MAX polishing deg.	270°
Amps	10A
Power	1200 W
Tool weight	6.8 lbs
QUICK-R™ front nut	30-B 020

DRUM SANDER

QUICK-STEP LINE-MATE III™

Order no. 30-A 268



Linear finishing made easy

The Line-Mate III™ is a versatile variable speed tool that allows you to quickly and easily apply a wide range of linear finishes to metal surfaces. Its powerful motor will help you complete even the toughest jobs with ease. RPM remains constant under load for a consistent and uniform finish every time. When you have a project that requires a linear scratch pattern applied to the surface, trust Line-Mate to get the job done quickly and efficiently.

LINE-MATE III™ SYSTEM

Order no. 30-A 269

Includes:

- 1 Line-Mate III™ with standard equipment plus carrying case
- 1 pneumatic drum (07-F 051)
- 6 cloth drum belts (2 each grit: 60: 07-F 506, 80: 07-F 508 and 120: 07-F 511)
- 2 BLENDEX drum belts (Coarse: 07-H 502, medium: 07-H 503)
- 1 TWO-IN-ONE drum (4 ¼" x 4": 07-K 342)
- 1 BLENDEX drum (4 ¼" x 4" medium: 07-M 343)



Description	QUICK-STEP LINE-MATE III™
Model name	6268C
Order No.	30-A 268
Lock-on switch	√
AC/DC compatibility	AC only
Soft-Start™	√
DYNAMAX™ RPM monitoring	√
POWERGUARD™ overheat protection	√
DIALSPEED™ variable RPM selector	√
Spindle	5/8" - 11
RPM no-load	1,000 to 3,800
Amps	12.4 A
Power	1500 W
Weight	6 lbs
Max. wheel dimensions	4 ½" diameter x 4" length
Standard equipment	
Side handle	30-B 075
Manual clamping nut	30-B 037
Pin key wrench	48-Z 148
Inner flange	30-B 057

POINT GRINDER

DIALSPEED™ 6141

Order no. 30-A 141

For fitting and finishing work

The convenient design of this very popular point grinder results in increased performance and operator comfort to let you reach new levels of productivity. Proven electronics and the quality construction of the motor deliver more power to the spindle while the ergonomic housing minimizes fatigue. This tool is the perfect companion to our premium carbide burs for any deburring or shaping applications.

SPEED 1	10,000 rpm
SPEED 2	14,000 rpm
SPEED 3	18,500 rpm
SPEED 4	22,000 rpm
SPEED 5	26,000 rpm
SPEED 6	30,500 rpm



Description	DIALSPEED™ 6141
Model name	6141E
Order No.	30-A 141
Lock-on switch	√
AC/DC compatibility	AC compatibility only
Soft-Start™	√
Restart protection	√
DYNAMAX™ RPM monitoring	√
POWERGUARD™ overheat protection	√
DIALSPEED™ variable RPM selector	√
Collet	¼"
RPM no-load	10,000 to 30,500
Amps	6.4 A
Power	710 W
Tool weight	4.2 lbs
Tool length	13.75"
Maximum wheel diameter	1.5"
Standard equipment	
¼ collet	30-B 046
Spanner	48-Z 019
Optional equipment	
Cutting guard	30-B 051

STRAIGHT GRINDER

DIALSPEED™ 6145

Order no. 30-A 145

For finishing, brushing and polishing work

Our Dialspeed™ Straight Grinder operates at a lower RPM range, making it the perfect companion for mounted flap wheels or wire brushes for brushing, finishing or polishing applications. The newly designed planetary gears allow you to get closer to the workpiece, producing a uniform and straight finish. This industrial power tool is built to last and also features a side handle for increased control in applications requiring a delicate touch.



SPEED 1	2,500 rpm
SPEED 2	4,000 rpm
SPEED 3	5,500 rpm
SPEED 4	7,000 rpm
SPEED 5	8,000 rpm
SPEED 6	8,700 rpm

Description	DIALSPEED™ STRAIGHT GRINDER 6145
Model name	6145E
Order No.	30-A 145
Lock-on switch	✓
AC/DC compatibility	AC compatibility only
Soft-Start™	✓
Restart protection	✓
DYNAMAX™ RPM monitoring	✓
POWERGUARD™ overheat protection	✓
DIALSPEED™ variable RPM selector	✓
Collet	¼"
RPM no-load	2,500 to 8,700
Amps	8.5 A
Power	950 W
Tool weight	4.3 lbs
Tool length	14"
Maximum wheel diameter	1.5"
Standard equipment	
Side handle	48-L 555
¼ collet	30-B 046
Spanner	48-Z 019
Optional equipment	
Cutting guard	30-B 051