

PART NUMBER	CYLINDER BORE	OUTSIDE DIAMETER	ROD DIAMETER	*A	B	C	D	*E	F	G	H	I	J	K	PORTS*
CL15-S	1.50"	1.875"	1.00"	8.25"	1.62"	0.87"	1.37"	2.25"	1.37"	1.50"	0.76"	-	0.93"	1.87"	SAE 4
CL20-S	2.00"	2.375"	1.25"	10.25"	2.12"	1.12"	2.12"	3.12"	2.12"	2.00"	1.01"	-	1.00"	2.06"	SAE6
CL25-S	2.50"	2.875"	1.50"	10.25"	2.12"	1.12"	2.12"	3.12"	2.12"	2.00"	1.01"	-	0.81"	2.18"	SAE 8
CL30-S	3.00"	3.50"	1.50"	10.25"	2.12"	1.12"	2.12"	3.12"	2.12"	2.00"	1.01"	-	0.81"	2.18"	SAE 8
CL35-S	3.50"	4.00"	1.75"	10.25"	2.37"	1.12"	2.00"	3.12"	2.12"	2.00"	1.01"	2.12"	0.93"	2.18"	SAE 8
CL40-S	4.00"	4.50"	2.00"	10.25"	2.37"	1.12"	1.75"	3.12"	2.00"	2.00"	1.01"	2.00"	1.06"	2.18"	SAE 8
CL50-S	5.00"	5.50"	2.50"	13.00"	3.12"	1.62"	2.25"	3.62"	2.25"	3.00"	1.51"	-	1.37"	2.75"	SAE 12

1. FOR 8" STROKE : A = 12.25" (2" TO 4" BORE)
 2. FOR 8" STROKE : E = 5.12" (2" TO 4" BORE)
 * NPT PORTS ARE ALSO AVAILABLE FROM 1.5" TO 4" BORE CYLINDERS


MAXIMUM RETRACTED WORKING PRESSURE : 3000 psi
 MAXIMUM EXTENDED WORKING PRESSURE : SEE TABLE
 RETRACTED AND STROKE TOLERANCE ± 1/8"

WELDED FEMALE CLEVIS TYPE									
PART NUMBER	BORE & STROKE	DIMENSIONS		ROD DIAMETER	PIN SIZE	PORTS*	COLUMN LOADS (LBS)	PRESSURE (PSI)	WEIGHT (LBS)
		RETRACTED	EXTENDED						
CL1504-S	1.5" X 4"	12-1/4"	16-1/4"	1"	3/4"	SAE 4	5300	3000	8
CL1506-S	1.5" X 6"	14-1/4"	20-1/4"						
CL1508-S	1.5" X 8"	16-1/4"	24-1/4"						
CL1510-S	1.5" X 10"	18-1/4"	28-1/4"						
CL1512-S	1.5" X 12"	20-1/4"	32-1/4"						
CL1514-S	1.5" X 14"	22-1/4"	36-1/4"						
CL1516-S	1.5" X 16"	24-1/4"	40-1/4"						
CL1518-S	1.5" X 18"	26-1/4"	44-1/4"						
CL1520-S	1.5" X 20"	28-1/4"	48-1/4"						
CL1524-S	1.5" X 24"	32-1/4"	56-1/4"						
CL2004-S	2" X 4"	14-1/4"	18-1/4"	1-1/4"	1"	SAE 6	9400	3000	14
CL2006-S	2" X 6"	16-1/4"	22-1/4"						
CL2008-S	2" X 8"	20-1/4"	28-1/4"						
CL2010-S	2" X 10"	20-1/4"	30-1/4"						
CL2012-S	2" X 12"	22-1/4"	34-1/4"						
CL2014-S	2" X 14"	24-1/4"	38-1/4"						
CL2016-S	2" X 16"	26-1/4"	42-1/4"						
CL2018-S	2" X 18"	28-1/4"	46-1/4"						
CL2020-S	2" X 20"	30-1/4"	50-1/4"						
CL2024-S	2" X 24"	34-1/4"	58-1/4"						
CL2028-S	2" X 28"	38-1/4"	66-1/4"						
CL2030-S	2" X 30"	40-1/4"	70-1/4"						
CL2032-S	2" X 32"	42-1/4"	74-1/4"						
CL2034-S	2" X 34"	44-1/4"	78-1/4"						
CL2036-S	2" X 36"	46-1/4"	82-1/4"						
CL2040-S	2" X 40"	50-1/4"	90-1/4"						
CL2048-S	2" X 48"	58-1/4"	106-1/4"						

* NPT PORTS ARE ALSO AVAILABLE.
 NOTE : COLUMN LOAD IS THE MAXIMUM PUSHING LOAD SUGGESTED USING A MINIMUM SAFETY FACTOR OF 2 AND BASED ON A PIN TO PIN MOUNTING CALCULATION.

HYDRO CUSTOM IS NOT RESPONSIBLE FOR INCORRECT RESULTS OBTAINED WITH FIGURES IN THIS DOCUMENT. INFORMATION IS FOR REFERENCE ONLY. NO OTHER CONDITIONS ARE EXPRESSED OR IMPLIED.

HYDRAULIC CYLINDERS






WELDED FEMALE CLEVIS TYPE


PART NUMBER	BORE & STROKE	DIMENSIONS		ROD DIAMETER	PIN SIZE	PORTS*	COLUMN LOADS (LBS)	PRESSURE (PSI)	WEIGHT (LBS)			
		RETRACTED	EXTENDED									
CL2504-S	2.5" X 4"	14-1/4"	18-1/4"	1-1/2"	1"	SAE 8	14700	3000	18			
CL2506-S	2.5" X 6"	16-1/4"	22-1/4"				14700	3000	20			
CL2508-S	2.5" X 8"	20-1/4"	28-1/4"				14700	3000	24			
CL2510-S	2.5" X 10"	20-1/4"	30-1/4"				14700	3000	25			
CL2512-S	2.5" X 12"	22-1/4"	34-1/4"				14700	3000	27			
CL2514-S	2.5" X 14"	24-1/4"	38-1/4"				14700	3000	29			
CL2516-S	2.5" X 16"	26-1/4"	42-1/4"				14700	3000	32			
CL2518-S	2.5" X 18"	28-1/4"	46-1/4"				14700	3000	34			
CL2520-S	2.5" X 20"	30-1/4"	50-1/4"				14700	3000	36			
CL2524-S	2.5" X 24"	34-1/4"	58-1/4"				14000	2800	40			
CL2528-S	2.5" X 28"	38-1/4"	66-1/4"				10800	2200	45			
CL2530-S	2.5" X 30"	40-1/4"	70-1/4"				9600	1900	47			
CL2532-S	2.5" X 32"	42-1/4"	74-1/4"				8600	1700	49			
CL2534-S	2.5" X 34"	44-1/4"	78-1/4"				7700	1500	52			
CL2536-S	2.5" X 36"	46-1/4"	82-1/4"				7000	1400	54			
CL2540-S	2.5" X 40"	50-1/4"	90-1/4"				5800	1100	58			
CL2548-S	2.5" X 48"	58-1/4"	106-1/4"				4200	800	67			
CL3004-S	3" X 4"	14-1/4"	18-1/4"				1-1/2"	1"	SAE 8	21200	3000	22
CL3006-S	3" X 6"	16-1/4"	22-1/4"							21200	3000	24
CL3008-S	3" X 8"	20-1/4"	28-1/4"							21200	3000	27
CL3010-S	3" X 10"	20-1/4"	30-1/4"	21200	3000	29						
CL3012-S	3" X 12"	22-1/4"	34-1/4"	21200	3000	31						
CL3014-S	3" X 14"	24-1/4"	38-1/4"	21200	3000	34						
CL3016-S	3" X 16"	26-1/4"	42-1/4"	21200	3000	36						
CL3018-S	3" X 18"	28-1/4"	46-1/4"	21200	3000	39						
CL3020-S	3" X 20"	30-1/4"	50-1/4"	18800	2600	41						
CL3024-S	3" X 24"	34-1/4"	58-1/4"	14000	1900	46						
CL3028-S	3" X 28"	38-1/4"	66-1/4"	10800	1500	51						
CL3030-S	3" X 30"	40-1/4"	70-1/4"	9600	1300	53						
CL3032-S	3" X 32"	42-1/4"	74-1/4"	8600	1200	56						
CL3034-S	3" X 34"	44-1/4"	78-1/4"	7700	1100	58						
CL3036-S	3" X 36"	46-1/4"	82-1/4"	7000	900	61						
CL3504-S	3.5" X 4"	14-1/4"	18-1/4"	1-3/4"	1"	SAE 8				28800	3000	27
CL3506-S	3.5" X 6"	16-1/4"	22-1/4"				28800	3000	30			
CL3508-S	3.5" X 8"	20-1/4"	28-1/4"				28800	3000	35			
CL3510-S	3.5" X 10"	20-1/4"	30-1/4"				28800	3000	36			
CL3512-S	3.5" X 12"	22-1/4"	34-1/4"				28800	3000	39			
CL3514-S	3.5" X 14"	24-1/4"	38-1/4"				28800	3000	42			
CL3516-S	3.5" X 16"	26-1/4"	42-1/4"				28800	3000	46			
CL3518-S	3.5" X 18"	28-1/4"	46-1/4"				28800	3000	49			
CL3520-S	3.5" X 20"	30-1/4"	50-1/4"				28800	3000	52			
CL3524-S	3.5" X 24"	34-1/4"	58-1/4"				26000	2700	58			
CL3528-S	3.5" X 28"	38-1/4"	66-1/4"				20100	2000	64			
CL3530-S	3.5" X 30"	40-1/4"	70-1/4"				17900	1800	67			
CL3532-S	3.5" X 32"	42-1/4"	74-1/4"				16000	1600	70			
CL3534-S	3.5" X 34"	44-1/4"	78-1/4"				14400	1500	73			
CL3536-S	3.5" X 36"	46-1/4"	82-1/4"				13000	1300	76			

* NPT PORTS ARE ALSO AVAILABLE.

NOTE : COLUMN LOAD IS THE MAXIMUM PUSHING LOAD SUGGESTED USING A MINIMUM SAFETY FACTOR OF 2 AND BASED ON A PIN TO PIN MOUNTING CALCULATION.

HYDRO CUSTOM IS NOT RESPONSIBLE FOR INCORRECT RESULTS OBTAINED WITH FIGURES IN THIS DOCUMENT. INFORMATION IS FOR REFERENCE ONLY. NO OTHER CONDITIONS ARE EXPRESSED OR IMPLIED.





WELDED FEMALE CLEVIS TYPE									
PART NUMBER	BORE & STROKE	DIMENSIONS		ROD DIAMETER	PIN SIZE	PORTS*	COLUMN LOADS (lbs)	PRESSURE (psi)	WEIGHT (lbs)
		RETRACTED	EXTENDED						
CL4004-S	4" X 4"	14-1/4"	18-1/4"	2"	1"	SAE 8	37600	3000	33
CL4006-S	4" X 6"	16-1/4"	22-1/4"				37600	3000	37
CL4008-S	4" X 8"	20-1/4"	28-1/4"				37600	3000	42
CL4010-S	4" X 10"	20-1/4"	30-1/4"				37600	3000	44
CL4012-S	4" X 12"	22-1/4"	34-1/4"				37600	3000	48
CL4014-S	4" X 14"	24-1/4"	38-1/4"				37600	3000	52
CL4016-S	4" X 16"	26-1/4"	42-1/4"				37600	3000	55
CL4018-S	4" X 18"	28-1/4"	46-1/4"				37600	3000	59
CL4020-S	4" X 20"	30-1/4"	50-1/4"				37600	3000	63
CL4024-S	4" X 24"	34-1/4"	58-1/4"				37600	3000	70
CL4028-S	4" X 28"	38-1/4"	66-1/4"				34300	2700	77
CL4030-S	4" X 30"	40-1/4"	70-1/4"				30500	2400	81
CL4032-S	4" X 32"	42-1/4"	74-1/4"				27300	2100	85
CL4034-S	4" X 34"	44-1/4"	78-1/4"				24600	1900	89
CL4036-S	4" X 36"	46-1/4"	82-1/4"				22200	1700	92
CL5004-S	5" X 4"	17"	21"	2-1/2"	1-1/2"	SAE 12	58900	3000	64
CL5006-S	5" X 6"	19"	25"				58900	3000	69
CL5008-S	5" X 8"	21"	29"				58900	3000	74
CL5010-S	5" X 10"	23"	33"				58900	3000	79
CL5012-S	5" X 12"	25"	37"				58900	3000	84
CL5014-S	5" X 14"	27"	41"				58900	3000	89
CL5016-S	5" X 16"	29"	45"				58900	3000	95
CL5018-S	5" X 18"	31"	49"				58900	3000	100
CL5020-S	5" X 20"	33"	53"				58900	3000	105
CL5024-S	5" X 24"	37"	61"				58900	3000	115
CL5028-S	5" X 28"	41"	69"				58900	3000	125
CL5030-S	5" X 30"	43"	73"				58900	3000	130
CL5032-S	5" X 32"	45"	77"				58900	3000	135
CL5034-S	5" X 34"	47"	81"				56100	2800	141
CL5036-S	5" X 36"	49"	85"				50900	2500	146
CL5040-S	5" X 40"	53"	93"	42500	2100	156			
CL5048-S	5" X 48"	61"	109"	30900	1500	176			

HYDRO CUSTOM IS NOT RESPONSIBLE FOR INCORRECT RESULTS OBTAINED WITH FIGURES IN THIS DOCUMENT. INFORMATION IS FOR REFERENCE ONLY. NO OTHER CONDITIONS ARE EXPRESSED OR IMPLIED.