

PART NUMBER	CYLINDER BORE	OUTSIDE DIAMETER	ROD DIAMETER	A	B	C	D	E	F	G	H	PORTS
BU15-S	1.50"	1.875"	1.00"	8.00"	1.25"	0.76"	2.62"	2.25"	2.00"	1.06"	1.87"	SAE 4
BU20-S	2.00"	2.375"	1.25"	8.00"	1.50"	1.01"	2.25"	2.75"	2.25"	1.00"	2.06"	SAE 6
BU25-S	2.50"	2.875"	1.50"	8.00"	1.50"	1.01"	2.25"	3.25"	2.25"	0.81"	2.18"	SAE 8
BU30-S	3.00"	3.50"	1.50"	8.00"	1.50"	1.01"	2.25"	3.75"	2.25"	0.81"	2.18"	SAE 8
BU35-S	3.50"	4.00"	1.75"	10.00"	2.00"	1.26"	4.00"	4.25"	2.25"	0.81"	2.18"	SAE 8
BU40-S	4.00"	4.50"	2.00"	10.00"	2.25"	1.51"	3.75"	4.75"	2.50"	0.81"	2.18"	SAE 8
BU50-S	5.00"	5.50"	2.50"	12.00"	3.00"	**1.76"	3.50"	5.75"	3.25"	1.25"	2.75"	SAE 12

** PIN SIZE WITH INSERT, 2" WHEN REMOVED
 MAXIMUM RETRACTED WORKING PRESSURE : 3000 psi

MAXIMUM EXTENDED WORKING PRESSURE : SEE TABLE
 RETRACTED AND STROKE TOLERANCE ± 1/8"


WELDED BUSHING

PART NUMBER	BORE & STROKE	DIMENSIONS		ROD DIAMETER	PIN SIZE	PORTS*	COLUMN LOADS (LBS)	PRESSURE (PSI)	WEIGHT (LBS)
		RETRACTED	EXTENDED						
BU1504-S	1.5" X 4"	12"	16"	1"	3/4"	SAE 4	5300	3000	8
BU1506-S	1.5" X 6"	14"	20"				5300	3000	9
BU1508-S	1.5" X 8"	16"	24"				5300	3000	10
BU1510-S	1.5" X 10"	18"	28"				5300	3000	12
BU1512-S	1.5" X 12"	20"	32"				5300	3000	13
BU1514-S	1.5" X 14"	22"	36"				5300	3000	14
BU1516-S	1.5" X 16"	24"	40"				5300	3000	15
BU1518-S	1.5" X 18"	26"	44"				4800	2700	17
BU1520-S	1.5" X 20"	28"	48"				4000	2300	18
BU1524-S	1.5" X 24"	32"	56"				3000	1700	20
BU2004-S	2" X 4"	12"	16"	1-1/4"	1"	SAE 6	9400	3000	12
BU2006-S	2" X 6"	14"	20"				9400	3000	13
BU2008-S	2" X 8"	16"	24"				9400	3000	15
BU2010-S	2" X 10"	18"	28"				9400	3000	17
BU2012-S	2" X 12"	20"	32"				9400	3000	19
BU2014-S	2" X 14"	22"	36"				9400	3000	20
BU2016-S	2" X 16"	24"	40"				9400	3000	22
BU2018-S	2" X 18"	26"	44"				9400	3000	24
BU2020-S	2" X 20"	28"	48"				9400	3000	25
BU2024-S	2" X 24"	32"	56"				7300	2300	29
BU2028-S	2" X 28"	36"	64"				5600	1700	32
BU2030-S	2" X 30"	38"	68"				4900	1500	34
BU2032-S	2" X 32"	40"	72"				4400	1400	35
BU2036-S	2" X 36"	44"	80"				3500	1100	39
BU2040-S	2" X 40"	48"	88"				2900	900	42
BU2048-S	2" X 48"	56"	104"				2100	600	49

* NPT PORTS ARE ALSO AVAILABLE.

NOTE : COLUMN LOAD IS THE MAXIMUM PUSHING LOAD SUGGESTED USING A MINIMUM SAFETY FACTOR OF 2 AND BASED ON A PIN TO PIN MOUNTING CALCULATION.


HYDRO CUSTOM IS NOT RESPONSIBLE FOR INCORRECT RESULTS OBTAINED WITH FIGURES IN THIS DOCUMENT. INFORMATION IS FOR REFERENCE ONLY. NO OTHER CONDITIONS ARE EXPRESSED OR IMPLIED.



WELDED BUSHING									
PART NUMBER	BORE & STROKE	DIMENSIONS		ROD DIAMETER	PIN SIZE	PORTS*	COLUMN LOAD (LBS)	PRESSURE (PSI)	WEIGHT (LBS)
		RETRACTED	EXTENDED						
BU2504-S	2.5" X 4"	12"	16"	1-1/2"	1"	SAE 8	14700	3000	16
BU2506-S	2.5" X 6"	14"	20"				14700	3000	18
BU2508-S	2.5" X 8"	16"	24"				14700	3000	20
BU2510-S	2.5" X 10"	18"	28"				14700	3000	22
BU2512-S	2.5" X 12"	20"	32"				14700	3000	24
BU2514-S	2.5" X 14"	22"	36"				14700	3000	27
BU2516-S	2.5" X 16"	24"	40"				14700	3000	29
BU2518-S	2.5" X 18"	26"	44"				14700	3000	31
BU2520-S	2.5" X 20"	28"	48"				14700	3000	33
BU2524-S	2.5" X 24"	32"	56"				14700	3000	38
BU2528-S	2.5" X 28"	36"	64"				11600	2300	42
BU2530-S	2.5" X 30"	38"	68"				10300	2100	45
BU2532-S	2.5" X 32"	40"	72"				9200	1800	47
BU2536-S	2.5" X 36"	44"	80"				7400	1500	51
BU2540-S	2.5" X 40"	48"	88"				6100	1200	56
BU2548-S	2.5" X 48"	56"	104"				4400	800	65
BU3004-S	3" X 4"	12"	16"	1-1/2"	1"	SAE 8	21200	3000	19
BU3006-S	3" X 6"	14"	20"				21200	3000	22
BU3008-S	3" X 8"	16"	24"				21200	3000	24
BU3010-S	3" X 10"	18"	28"				21200	3000	27
BU3012-S	3" X 12"	20"	32"				21200	3000	29
BU3014-S	3" X 14"	22"	36"				21200	3000	32
BU3016-S	3" X 16"	24"	40"				21200	3000	34
BU3018-S	3" X 18"	26"	44"				21200	3000	36
BU3020-S	3" X 20"	28"	48"				20700	2900	39
BU3024-S	3" X 24"	32"	56"				15200	2100	44
BU3028-S	3" X 28"	36"	64"				11600	1600	49
BU3030-S	3" X 30"	38"	68"				10300	1400	51
BU3032-S	3" X 32"	40"	72"				9200	1300	53
BU3036-S	3" X 36"	44"	80"				7400	1000	58
BU3040-S	3" X 40"	48"	88"				6100	800	63
BU3048-S	3" X 48"	56"	104"				4400	600	73
BU3504-S	3.5" X 4"	14"	18"	1-3/4"	1-1/4"	SAE 8	28800	3000	27
BU3506-S	3.5" X 6"	16"	22"				28800	3000	30
BU3508-S	3.5" X 8"	18"	26"				28800	3000	33
BU3510-S	3.5" X 10"	20"	30"				28800	3000	36
BU3512-S	3.5" X 12"	22"	34"				28800	3000	39
BU3514-S	3.5" X 14"	24"	38"				28800	3000	42
BU3516-S	3.5" X 16"	26"	42"				28800	3000	45
BU3518-S	3.5" X 18"	28"	46"				28800	3000	48
BU3520-S	3.5" X 20"	30"	50"				28800	3000	51
BU3524-S	3.5" X 24"	34"	58"				26200	2700	57
BU3528-S	3.5" X 28"	38"	66"				20200	2100	63
BU3530-S	3.5" X 30"	40"	70"				18000	1800	66
BU3532-S	3.5" X 32"	42"	74"				16100	1600	69
BU3536-S	3.5" X 36"	46"	82"				13100	1300	75
BU3540-S	3.5" X 40"	50"	90"				10900	1100	81
BU3548-S	3.5" X 48"	58"	106"				7800	800	94

* NPT PORTS ARE ALSO AVAILABLE.
NOTE : COLUMN LOAD IS THE MAXIMUM PUSHING LOAD SUGGESTED USING A MINIMUM SAFETY FACTOR OF 2 AND BASED ON A PIN TO PIN MOUNTING CALCULATION.

HYDRO CUSTOM IS NOT RESPONSIBLE FOR INCORRECT RESULTS OBTAINED WITH FIGURES IN THIS DOCUMENT. INFORMATION IS FOR REFERENCE ONLY. NO OTHER CONDITIONS ARE EXPRESSED OR IMPLIED.



WELDED BUSHING

PART NUMBER	BORE & STROKE	DIMENSIONS		ROD DIAMETER	PIN SIZE	PORTS*	COLUMN LOAD (LBS)	PRESSURE (PSI)	WEIGHT (LBS)			
		RETRACTED	EXTENDED									
BU4004-S	4" X 4"	14"	18"	2"	1-1/2"	SAE 8	37600	3000	34			
BU4006-S	4" X 6"	16"	22"				37600	3000	38			
BU4008-S	4" X 8"	18"	26"				37600	3000	41			
BU4010-S	4" X 10"	20"	30"				37600	3000	45			
BU4012-S	4" X 12"	22"	34"				37600	3000	49			
BU4014-S	4" X 14"	24"	38"				37600	3000	52			
BU4016-S	4" X 16"	26"	42"				37600	3000	56			
BU4018-S	4" X 18"	28"	46"				37600	3000	59			
BU4020-S	4" X 20"	30"	50"				37600	3000	63			
BU4024-S	4" X 24"	34"	58"				37600	3000	70			
BU4028-S	4" X 28"	38"	66"				34600	2700	78			
BU4030-S	4" X 30"	40"	70"				30700	2400	81			
BU4032-S	4" X 32"	42"	74"				27500	2100	85			
BU4036-S	4" X 36"	46"	82"				22400	1700	92			
BU4040-S	4" X 40"	50"	90"				18600	1400	99			
BU4048-S	4" X 48"	58"	106"				13400	1000	114			
BU5004-S	5" X 4"	16"	20"				2-1/2"	1-3/4"	SAE 12	58900	3000	64
BU5006-S	5" X 6"	18"	24"							58900	3000	69
BU5008-S	5" X 8"	20"	28"	58900	3000	75						
BU5010-S	5" X 10"	22"	32"	58900	3000	80						
BU5012-S	5" X 12"	24"	36"	58900	3000	85						
BU5014-S	5" X 14"	26"	40"	58900	3000	90						
BU5016-S	5" X 16"	28"	44"	58900	3000	96						
BU5018-S	5" X 18"	30"	48"	58900	3000	101						
BU5020-S	5" X 20"	32"	52"	58900	3000	106						
BU5024-S	5" X 24"	36"	60"	58900	3000	116						
BU5028-S	5" X 28"	40"	68"	58900	3000	126						
BU5030-S	5" X 30"	42"	72"	58900	3000	131						
BU5032-S	5" X 32"	44"	76"	58900	3000	136						
BU5036-S	5" X 36"	48"	84"	52100	2600	147						
BU5040-S	5" X 40"	52"	92"	43400	2200	157						
BU5048-S	5" X 48"	60"	108"	31500	1600	177						

* NPT PORTS ARE ALSO AVAILABLE.

NOTE : COLUMN LOAD IS THE MAXIMUM PUSHING LOAD SUGGESTED USING A MINIMUM SAFETY FACTOR OF 2 AND BASED ON A PIN TO PIN MOUNTING CALCULATION.

HYDRO CUSTOM IS NOT RESPONSIBLE FOR INCORRECT RESULTS OBTAINED WITH FIGURES IN THIS DOCUMENT. INFORMATION IS FOR REFERENCE ONLY. NO OTHER CONDITIONS ARE EXPRESSED OR IMPLIED.