

BAYONET FILLER BREATHERS

- ZINC PLATED CAP
- 160 GPM MAXIMUM FLOW
- 40 MICRONS (10 MICRONS AVAILABLE)
- STAINLESS STEEL BASKET (NYLON AVAILABLE)


PART NUMBER	DESCRIPTION
57XL-40	STANDARD MODEL
AS-57XL-40	57XL40 WITH ANTI-SPLASH
LC-57XL-40	57XL40 WITH LOCKING CAP
57XL-40-P5	57XL40 PRESSURIZED TO 5 PSI



METAL THREADED BREATHERS

- ZINC PLATED CAP
- 40 MICRONS (10 MICRONS AVAILABLE)

PART NUMBER	NPT THREAD	MAX GPM	DIMENSIONS		
			A	B	C
BF-4	1/4"	28	1.4"	1.9"	0.7"
BF-6	3/8"				
BF-8	1/2"	245	2.6"	2.9"	0.9"
BF-12	3/4"	280	2.6"	3"	1.1"
BF-12-16 **			3"	3.3"	1.4"
BF-16	1"	525			



\*\* CAN BE PRESSURIZED TO 5 PSI. PART NO IS BF-12-16-P5

NYLON THREADED BREATHERS

- 40 MICRONS (10 MICRONS AVAILABLE)
- ANTI-SPLASH & DIPSTICK OPTIONS ARE AVAILABLE

PART NUMBER	NPT THREAD	DIMENSIONS			
		A	B	C	D
NY-4	1/4"	1.2"	1.4"	0.8"	0.6"
NY-6	3/8"				
NY-8	1/2"	1.6"	1.5"	0.9"	0.6"
AS-NY-8	1/2" ANTI-SPLASH				
NY-12	3/4"	1.8"	1.5"	0.9"	0.6"
NY-7-12		2.8"	2"	1.4"	0.7"
AS-NY-7-12	3/4" ANTI-SPLASH	1.8"	1.5"	0.9"	0.6"
NY-16	1"				
NY-7-16	1 1/4"	2.8"	2.2"	1.4"	0.8"
NY-7-20					
AS-NY-7-20-DIP5"	1 1/4" 5" DIPSTICK + ANTI-SPLASH				

