

# HIGH PRESSURE HOSES & HOSE REELS

## Gray Non-Marking 6000 psi

Part No.	Pressure	Length
HW506000GR	6000 psi	50'
HW1006000GR		100'
HW1506000GR		150'
HW2006000GR		200'



- 250°F Max Temperature
- 3/8" NPT-M Solid End/Swivel End
- Steel Wire Braid
- Smooth Wrap

## Black 6000 psi

Part No.	Pressure	Length
HW506000	6000 psi	50'
HW1006000		100'



- 4000 psi Max Pressure
- 350°F Max Temperature
- 3/8" NPT-M Solid End/Swivel End
- Steel Wire Braid
- Smooth Wrap

## Economical Hose Reel

Part No.	Capacity	ID
HR50N	50'	3/8"
HR100N	100'	3/8"
HR150N	150'	3/8"
HR200N	200'	3/8"



- 3500 psi Max Pressure
- 185°F Max Temperature
- 3/8" NPT-M Inlet
- 3/8" NPT-F Outlet

## Carry Handle Hose Reel

Part No.	Capacity	ID
HR100CH	100'	3/8"



- 5000 psi Rated Pressure
- 185°F Max Temperature
- 1/4" NPT-M Inlet
- 3/8" NPT-F Outlet

## HR50150HD - Heavy Duty

Part No.	Capacity	ID
HR50150HD	150'	3/8"



- 5000 psi Rated Pressure
- 250°F Max Temperature
- 3/8" NPT-M Inlet
- 3/8" NPT-F Outlet

## PW2 & PWK400 Wall Mount Kit

Part No.	Capacity	ID
PW2	150'	3/8"
PWK400	Wall Mount Kit	



- 4000 psi Rated Pressure
- 250°F Max Temperature
- 1/2" NPT-F Inlet
- 3/8" NPT-F Outlet

## SHR50150 - Stainless Steel

Part No.	Capacity	ID
SHR50150	150'	3/8"



Stainless Steel

- 5000 psi Rated Pressure
- 400°F Max Temperature
- 3/8" NPT-F Inlet/Outlet

## DHRP50150 - Heavy Duty Pedestal Mount

Part No.	Capacity	ID
DHRP50150	150'	3/8"



- 5000 psi Rated Pressure
- 185°F Max Temperature
- 3/8" NPT-F Inlet
- 3/8" NPT-M Outlet

## DHRA - Heavy Duty 'A' Frame Hose Reel

Part No.	Capacity	ID
DHRA50150	150'	3/8"
DHRA50300	300'	3/8"



- 5000 psi Rated Pressure
- 300°F Max Temperature
- 1/2" NPT-F Inlet/Outlet

## Hannay Series 1000 & 1000SS Hose Reel

Part No.	Capacity	ID
10141416**	75'	3/8"
10161416**	100'	3/8"
10201416**	150'	3/8"



\*\* Add SS to Part No. to specify Stainless Steel

- 3000 psi Max Pressure
- 400°F Max Temperature
- 3/8" NPT-F Inlet/Outlet
- Handles Hose ID 1/4" up to 3/8"

Stainless Steel

# HOSE REELS

## 1100 · GH1100 - Portable Hose Reel

Part No.	Pressure	Capacity	ID
1100	3000 psi	275'	3/8"
GH1100	300 psi	275'	3/8"

- 400°F Max Temperature
- 1/2" NPT-F Inlet/Outlet
- Handles Hose ID 3/8" up to 1"
- Portable with Rubber Tires
- GH1100 Garden Hose Model:
  - Threaded Outlet
  - 5' Lead in Hose
  - Hose End Clips



## AT1200 · GHAT1200 - Portable Hose Reel

Part No.	Pressure	Capacity	ID
AT1200	2000 psi	350'	1/2"
GHAT1200	300 psi	350'	1/2"

- 250°F Max Temperature
- 1" NPT-F Inlet/Outlet
- Handles Hose ID 3/8" up to 1"
- Portable with Pneumatic Tires
- GHAT1200 Garden Hose Model:
  - Threaded Outlet
  - 5' Lead in Hose
  - Hose End Clips



## 1500 Series - Manual or Power Hose Reel

Part No.	Capacity	ID
15141718	75'	3/8"
15201718	175'	3/8"
15261718	300'	3/8"
15301718	375'	3/8"
15361718	475'	1/2"

- 3000 psi Max Pressure
- 400°F Max Temperature
- 1/2" NPT-F Inlet/Outlet
- Handles Hose ID 1/4" up to 5/8"
- Specify Voltage for Power Hose Reel
  - E12V - 12 Volt No Switch
  - E24V - 24 Volt No Switch
  - E115V -115 Volt No Switch
  - HD - Hydraulic
  - A - Air



## 6000 Series - Manual or Power Hose Reel

Part No.	Capacity	ID
60241921	200'	1/2"
60321921	350'	1/2"
60242324	400'	1/2"
60302324	225'	3/4"
60382324	300'	3/4"
60162526	250'	1/2"
60222526	450'	1/2"
60282526	275'	3/4"
60183031	400'	1/2"
60243031	350'	3/4"
60283031	450'	3/4"

- 2000 psi Rated Pressure
- 250°F Max Temperature
- 1" NPT-F Inlet/Outlet
- Handles Hose ID 1/2" up to 1"
- Specify Voltage for Power Hose Reel
  - EP12V - 12 volt with Switch and Solenoid
  - EP24V - 24 volt with Switch and Solenoid
  - E115V - 115 volt with Switch and Solenoid
  - HD - Hydraulic
  - A - Air



## HR65SR - Economical Spring Rewind

Part No.	Pressure	Capacity	ID
HR65SR	4000 psi	65'	3/8"

- 210°F Max Temperature
- 3/8" NPT-F Inlet
- 3/8" NPT-M Outlet
- Includes 65' of High Pressure Hose



## N700 - Spring Rewind

Part No.	Capacity	ID
N71614168C	25'	3/8"
N7161617CSR	35'	3/8"
N7161920J	50'	3/8"
N7162324J	65'	3/8"
N7162324G	100'	1/2"
N7162526B	75'	3/8"
N7182526G	100'	3/8"
718302120D	150'	3/8"

- 3000 psi Rated Pressure
- 250°F Max Temperature
- 1/2" NPT-F Inlet/Outlet
- Handles Hose ID 1/4" up to 1/2"



## 6100 Series - Power Rewind

Part No.	Capacity	ID
61182324	400'	3/8"
61222324	600'	3/8"
61162526	400'	3/8"
61182526	475'	3/8"
61222526	700'	3/8"
61163031	600'	3/8"
61183031	675'	3/8"

- 5000 psi Rated Pressure
- 250°F Max Temperature
- 1/2" NPT-F Inlet/Outlet
- Handles Hose ID 3/8" and 1/2"
- Specify Voltage for Power Hose Reel
  - EP12V - 12 volt with Switch and Solenoid
  - EP24V - 24 volt with Switch and Solenoid
  - E115V - 115 volt with Switch and Solenoid
  - HD - Hydraulic
  - A - Air

