

FML01/LS12/LS12SS

Part No.	Description
FML01	Foamer Lance
LS12SS	Stainless Steel Foamer

- 2900 psi Max Pressure
- Up to 6.5 gpm Max Flow
- 140°F Max Temperature
- 1/4" BSP-F Inlet
- 1.5 mm Injector
- FML01 Pressed Strainer



LS10

Part No.	Description
LS10	Foamer Lance

- 2900 psi Max Pressure
- 6.5 gpm Max Flow
- 150°F Max Temperature
- 1/4" BSP-F Inlet
- LS10 Mesh Strainer



LS12 with Extension Injector

Part No.	Description
LS12	1.8 mm Nozzle

- 2900 psi Max Pressure
- 2.6 gpm Max Flow
- 140°F Max Temperature
- 1/4" BSP-F Inlet
- External Injector 3/8" BSP-M
- LS12 Pressed Strainer



FML01T/FML02T/LS12/LS12SS

Part No.	Description
FML01T	Foamer with 1L Tank
FML02T	Foamer with 2L Tank
LS12SS	Stainless Steel Foamer

- 2900 psi Max Pressure
- Up to 6.5 gpm Max Flow
- 140°F Max Temperature
- 1/4" BSP-F Inlet
- 1.5 mm Injector
- Replacement 1L tank 14650625P
- Replacement 2L tank 14650700P
- FML01T Pressed Strainer



LS10T/02T

Part No.	Description
LS10BL2	Foamer with 2L Tank

- 2900 psi Max Pressure
- 6.5 gpm Max Flow
- 150°F Max Temperature
- 3/8" BSP-M Inlet
- Replacement 2L Tank 14650700P
- LS10T/02T Mesh Strainer



RB31/LS1

Part No.	Description
RB35LS1	Low Pressure Foamer

- 173 psi Max Pressure
- 13.2 gpm Max Flow
- 120°F Max Temperature
- 1/2" BSP-F Inlet
- Replacement 2L Tank 14650700P



LS31 Foam Lance with Tank

Part No.	Description
LS31	Foamer with 1L Tank

- 2300 psi Max Pressure
- 5.3 gpm Max Flow
- 140°F Max Temperature
- 1/4" BSP-F Inlet
- 1.25 mm Nozzle
- Replacement 2L Tank 14650200P



Soap Shooter

Part No.	Description
SPS100145	4.0 Nozzle
SPS100146	4.5 Nozzle
SPS100147	5.0 Nozzle


- 5000 psi Max Pressure
- Adjustable Chemical Rate
- 140°F Max Temperature
- 1/4" QC Connection
- 30' Hose and Strainer



RPS SS Foam Ball Valves

Part No.	Description
29100000P	303 SS Handle (A)
29103000P	303 SS Butterfly (D)
29105000P	316 SS Handle (B)
29108000P	316 SS Butterfly (C)

- 350 psi Max Pressure
- 21 gpm Max Flow
- 195°F Max Temperature
- 1/2" BSP-F Inlet/Outlet
- Stainless Steel Ball Valves



RL34/RL82 - Foam Gun

Part No.	Inlet
RL34	1/2" BSP-F SW
RL82	1/2" BSP-F SW SS

- 1850 psi Rated Pressure
- 21 gpm Max Flow
- 320°F Max Temperature
- 1/2" BSP-F Outlet

