

QUICK CONNECT FITTINGS

QD Sockets - Brass Plated

Part No.	Pressure	Connection
QC7214	5000 psi	1/4" NPT-F
QC7210	5000 psi	1/4" NPT-M
QC7218	4000 psi	3/8" NPT-F
QC7217	4000 psi	3/8" NPT-M
QC7235	2200 psi	1/2" NPT-F
QC7230	2200 psi	1/2" NPT-M



- 175°F Max Temperature
- Standard O-rings
- EPR with Teflon Coating

QD Socket - 316 Stainless Steel

Part No.	Pressure	Connection
QDSS250F	6000 psi	1/4" NPT-F
QDSS250M	6000 psi	1/4" NPT-M
QDSS375F	5000 psi	3/8" NPT-F
QDSS375M	5000 psi	3/8" NPT-M
QDSS500F	5000 psi	1/2" NPT-F
QDSS500M	5000 psi	1/2" NPT-M



- 175°F Max Temperature
- Standard O-rings
- EPR with Teflon Coating

316 SS

QD Plug - Brass Plated

Part No.	Pressure	Connection
QC7193	5000 psi	1/4" NPT-F
QC7194	5000 psi	1/4" NPT-M
QC7195	4000 psi	3/8" NPT-F
QC7196	4000 psi	3/8" NPT-M



- 175°F Max Temperature
- Standard O-rings
- EPR with Teflon Coating

QD Plug - 316 Stainless Steel

Part No.	Pressure	Connection
PLSS250F	6000 psi	1/4" NPT-F
PLSS250M	6000 psi	1/4" NPT-M
PLSS375F	5000 psi	3/8" NPT-F
PLSS375M	5000 psi	3/8" NPT-M
QC7191	5000 psi	1/2" NPT-F
QC7190	5000 psi	1/2" NPT-M



- 175°F Max Temperature
- Standard O-rings
- EPR with Teflon Coating

316 SS

QD Plug - Hardened Stainless Steel

Part No.	Pressure	Connection
PLTC250F	5500 psi	1/4" NPT-F
PLTC250M	5500 psi	1/4" NPT-M
PLTC375F	5000 psi	3/8" NPT-F
PLTC375M	5000 psi	3/8" NPT-M



- 175°F Max Temperature
- Standard O-rings
- EPR with Teflon Coating

Stainless Steel

EGQC - Easy Grip Quick Couplers

Part No.	Connection
EGQC250F	QC 1/4" x 1/4" NPT-F
EGQC250M	QC 1/4" x 1/4" NPT-M
EGQC375F	QC 3/8" x 3/8" NPT-F
EGQC375M	QC 3/8" x 3/8" NPT-M



- 1/4" 5000 psi
- 3/8" 4000 psi Max Pressure
- 175°F Max Temperature
- Brass Construction

Replacement O Rings

Part No.	Size	Material
QC7109D13	1/4"	EPR
QC7109D14	3/8"	EPR
QC7109D37	1/2"	EPR
QC7109D26	1/4"	Viton
QC7109D40	3/8"	Viton
QC7109D42	1/2"	Viton



QC Assembly - (Sold Together)

Part No.	Pressure	Connection
NQC11	10,000 psi	3/8" NPT-F
NQC22	10,000 psi	1/2" NPT-F

- 175°F Max Temperature



Stainless Steel

QUICK COUPLERS & SCREW CONNECTORS

QCA - Interpump Screw Connectors

Part No.	Connection
QCA250M	1/4" BSP-M
QCA375M	3/8" BSP-M
QCA250F	1/4" BSP-F
QCA375F	3/8" BSP-F

- 3000 psi Max Pressure
- 10.5 gpm Max Flow
- 284°F Max Temperature
- Screw Type QC Part A



QCB - Interpump Quick Couplers

Part No.	Connection
QCB250M	1/4" BSP-M
QCB375M	3/8" BSP-M
QCB250F	1/4" BSP-F
QCB375F	3/8" BSP-F

- 3000 psi Max Pressure
- 10.5 gpm Max Flow
- 284°F Max Temperature
- Screw Type QC Part B



AR1A - PA Screw Connectors

Part No.	Connection
AR1AM375	3/8" BSP-M
AR1AM250	1/4" BSP-M
AR1AF375	3/8" BSP-F
AR1AF250	1/4" BSP-F

- 3650 psi Max Pressure
- 10.5 gpm Max Flow
- 320°F Max Temperature
- Brass Construction



AR1B - PA Quick Couplers

Part No.	Connection
AR1BM375	3/8" BSP-M
AR1BM250	1/4" BSP-M
AR1BF375	3/8" BSP-F
AR1BF250	1/4" BSP-F

- 3650 psi Max Pressure
- 10.5 gpm Max Flow
- 320°F Max Temperature
- Brass Construction



AR41 PA Quick Couplers

Part No.	Connection
AR41A	3/8" BSP-F
AR41B	3/8" BSP-F

- 3650 psi Max Pressure
- 10.5 gpm Max Flow
- 320°F Max Temperature
- 303 Stainless Steel Construction



303 SS

AR8 PA Quick Couplers

Part No.	Connection
26063040P	3/8" BSP-F
26065050P	3/8" BSP-M

- 5100 psi Max Pressure
- 8.0 gpm Max Flow
- 320°F Max Temperature
- Brass Construction



AR9 - PA Quick Couplers

Part No.	Connection
26094070P	1/2" BSP-M
26095070P	1/2" BSP-M

- 8700 psi Max Pressure
- 21.0 gpm Max Flow
- 320°F Max Temperature
- 303 Stainless Steel Construction



303 SS