

SCREWDRIVERS

Impact Clutch Screwdrivers



1/4"



CP2136

COMPACT,
FAST & EASY TO USE

FEATURES

- 1/4" Hex quick change
- Double rocking dog clutch
- Single hard reverse

BENEFITS

- Compact & Lightweight
- Low air consumption for a better efficiency
- Excellent for various MRO applications



1/4"



CP2141

COMPACT,
FAST & EASY TO USE

FEATURES

- 1/4" Hex bits
- Double rocking dog clutch
- Single hard reverse

BENEFITS

- Compact & Lightweight
- Low noise level for operator comfort
- Excellent for various MRO applications



CP2141



See accessories on pages 36

| MODEL | PART NUMBER | DRIVE | FREE SPEED | TORQUE RANGE | | | | NET WEIGHT | | LENGTH | | AIR CONS. @ LOAD | | AIR INLET |
|--------|--------------|-------|------------|--------------|----|-------|----|------------|------|--------|-----|------------------|-----|-----------|
| | | | | MIN. | | MAX. | | lb | kg | in. | mm | cfm | l/s | |
| | | in. | rpm | ft.lb | Nm | ft.lb | Nm | | | | | | | in. |
| CP2136 | 894 102 1360 | 1/4 | 10,000 | 5.93 | 8 | 15.5 | 21 | 1.50 | 0.68 | 7.28 | 185 | 6.78 | 3.2 | 1/4 |
| CP2141 | 894 102 1410 | 1/4 | 13,000 | 7.38 | 10 | 17.7 | 24 | 1.92 | 0.87 | 5.63 | 143 | 13.2 | 6.2 | 1/4 |

All models: Hose int. 3/8" (9.5mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool or on www.cp.com

Impact Screwdrivers



1/4" 



CP2780

COMPACT & HIGH SPEED
POSITIVE CLUTCH

FEATURES

- Reverse control at the trigger
- Progressive trigger
- Rubber grip

BENEFITS

- Perfectly designed for wood applications
- Operator can control clutch engagement for higher torque
- Good for prevailing torque applications



1/4" 



CP2042

COMPACT
& HIGH TORQUE

FEATURES

- Double rocking dog clutch
- Reversible
- Suspension bail included

BENEFITS

- High power delivered with controlled speed
- Comfortable handling with Ergo-grip
- Operator comfort
- with single handed



1/4" 



CP2036

LOW NOISE
& LIGHTWEIGHT

FEATURES

- Double rocking dog clutch
- Built-in power regulator
- Ergonomic with suspension bail

BENEFITS

- Low noise & lightweight
- Quick torque adjustment
- Excellent for soft type materials

CP2037

Similar features as CP2036 with higher torque



See accessories on pages 36

| MODEL | PART NUMBER | DRIVE | FREE SPEED | TORQUE RANGE | | | | NET WEIGHT | | LENGTH | | AIR CONS. @ LOAD | | AIR INLET |
|--------|--------------|-------|------------|--------------|-----|-------|----|------------|------|--------|-----|------------------|------|-----------|
| | | | | MIN. | | MAX | | lb | kg | in. | mm | cfm | l/s | |
| | | in. | rpm | ft.lb | Nm | ft.lb | Nm | | | | | | | in. |
| CP2780 | 615 192 2780 | 1/4 | 2,100 | N/A | N/A | 7.4 | 10 | 2.35 | 1.06 | 6.46 | 164 | 10 | 4.7 | 1/4 |
| CP2042 | 615 192 2042 | 1/4 | 5,600 | 4.4 | 6 | 30.2 | 41 | 2.25 | 1.02 | 5.90 | 152 | 27 | 12.7 | 1/4 |
| CP2036 | 615 192 2036 | 1/4 | 10,000 | 2.5 | 3.4 | 11.8 | 16 | 1.73 | 0.78 | 8.15 | 207 | 13 | 6.1 | 1/4 |
| CP2037 | 615 192 2037 | 1/4 | 10,000 | 13.3 | 18 | 20.7 | 28 | 1.81 | 0.82 | 8.15 | 207 | 13 | 6.1 | 1/4 |

All models: Hose int. 3/8" (9.5mm) - @90 PSI (@6.3 Bar)


Listed specifications are for reference only. Please check documents in each tool or on www.cp.com

SCREWDRIVERS

Kits, Spares & Accessories



TUNE-UP KITS



| MODEL | TUNE-UP KIT |
|--------|--------------|
| CP2036 | 894 020 8405 |
| CP2037 | 894 020 8401 |
| CP2041 | 894 020 8402 |
| CP2042 | 894 020 8406 |
| CP2136 | 894 017 0493 |
| CP2141 | 894 017 0516 |
| CP2755 | 205 050 7773 |
| CP2765 | 205 050 7803 |
| CP2780 | 205 051 6763 |

ACCESSORIES INCLUDED

| MODEL | DESCRIPTION | PART NUMBER |
|----------------|-----------------|--------------|
| CP2136, CP2141 | Suspension bail | 894 017 0488 |

OPTIONAL ACCESSORIES



REAR EXHAUST HOSE ASSEMBLY - NOISE REDUCER

| MODEL | DESCRIPTION | PART NUMBER |
|------------------------|---------------|--------------|
| CP2755, CP2765, CP2780 | Noise reducer | 205 051 6493 |



SIDE HANDLE

| MODEL | DESCRIPTION | PART NUMBER |
|------------------------|-------------|--------------|
| CP2755, CP2765, CP2780 | Side handle | 205 049 8553 |



STUD CLEANERS (Recommended with CP2755)

| PART NUMBER | DESCRIPTION | DIAMETER | | LENGTH | | REPLACEMENT BRUSHES (Sets of 5) |
|--------------|----------------------|----------|----|--------|----|---------------------------------|
| | | in. | mm | in. | mm | |
| 894 016 8858 | Stud Cleaner M20x37L | 0.79 | 20 | 1.46 | 37 | 894 016 9930 |
| 894 016 9793 | Stud Cleaner M22x37L | 0.87 | 22 | 1.46 | 37 | 894 016 9931 |
| 894 016 9794 | Stud Cleaner M24x37L | 0.94 | 24 | 1.46 | 37 | 894 016 9932 |
| 894 016 9927 | Stud Cleaner M20x60L | 0.79 | 20 | 2.36 | 60 | 894 016 9934 |
| 894 016 9928 | Stud Cleaner M22x60L | 0.87 | 22 | 2.36 | 60 | 894 016 9935 |
| 894 016 9929 | Stud Cleaner M24x60L | 0.94 | 24 | 2.36 | 60 | 894 016 9936 |
| 894 016 9795 | Stud Cleaner M30x60L | 1.18 | 30 | 2.36 | 60 | 894 016 9933 |

Did you know?

Rusted bolts have a bad impact on the clamping force!

Stud cleaners will preserve a good tightening!



BALANCERS

| BALANCER | LOAD RANGE | | STROKE | | NET WEIGHT | | PART NUMBER | CP TOOLS |
|-----------------------------|------------|---------|--------|-------|------------|-----|--------------|---|
| | lb. | kg | ft | mm | lb. | kg | | |
| CP9911 (up to 2.2lb/1kg) | 0.8-2.2 | 0.4-1.0 | 5.2 | 1,600 | 1.3 | 0.6 | 894 109 9110 | CP2036 / CP2037 CP2136 / CP2141 |
| CP9912 (up to 4.4lb/2kg) | 2.2-4.4 | 1.0-2.0 | 5.2 | 1,600 | 1.3 | 0.6 | 894 109 9120 | CP2041 / CP2042 / CP2755 / CP2765 / CP2780 |

Other balancers, see page 144-145

CLASSIC

Screwdrivers



1/4"



CP780

HIGH SPEED
& ROBUST

FEATURES

- External clutch adjustment
- Built-in 1/4" Female Hex quick-change
- Convenient single handed forward/reverse

BENEFITS

- High speed fastening for greater productivity
- Reliable & easy-to-adjust cushion clutch
- Ideal tool for general repair, wood, PVC & refurbishing applications



1/4"



CP781

HIGH TORQUE
& ROBUST

FEATURES

- External clutch adjustment
- Built-in 1/4" Female Hex quick-change
- Convenient single handed forward/reverse

BENEFITS

- Reliable & easy-to-adjust cushion clutch for powerful fastening
- Robust aluminum body & steel clutch housing
- Ideal tool for general assembly, metal, wood, PVC and refurbishing applications



See accessories on pages 102

| MODEL | PART NUMBER | OUTPUT DRIVE | FREE SPEED | TORQUE RANGE | | | | AVERAGE AIR CONS. | | AIR CONS. @ LOAD | | OVERALL LENGTH | | NET WEIGHT | | AIR INLET |
|-------|-------------|--------------|------------|--------------|------|-------|------|-------------------|-----|------------------|-----|----------------|-----|------------|------|-----------|
| | | | | MIN. | | MAX | | cfm | l/s | cfm | l/s | in. | mm | lb | kg | NPTF |
| | | in. | rpm | ft.lb | Nm | ft.lb | Nm | cfm | l/s | cfm | l/s | in. | mm | lb | kg | NPTF |
| CP780 | T025095 | 1/4 | 1,800 | 2.06 | 2.83 | 3.7 | 4.97 | 4 | 1.9 | 16 | 7.6 | 8.25 | 210 | 2.50 | 1.13 | 1/4" |
| CP781 | T025096 | 1/4 | 800 | 4.57 | 6.2 | 8.4 | 11.3 | 4 | 1.9 | 16 | 7.6 | 8.88 | 226 | 3.00 | 1.36 | 1/4" |

All models: Hose int. 3/8" (10 mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool.

Screwdrivers



1/4" 



CP782
HIGH TORQUE
& ROBUST

FEATURES

- External clutch adjustment
- Convenient single handed forward/reverse valve
- Progressive lever start and suspension bail

BENEFITS

- Reliable cushion clutch
- Comfortable use thanks to low weight
- Ideal tool for general assembly operations on metal, wood, PVC, or any repair applications



1/4" 



CP783
COMPACT
& HIGH SPEED

FEATURES

- External clutch adjustment
- Convenient one-hand forward/reverse valve
- Progressive lever start and suspension bail

BENEFITS

- Reliable cushion clutch
- Faster cycle times with 2000rpm
- Ideal tool for general assembly operations on metal, wood, PVC, or any repair applications



See accessories on pages 102

| MODEL | PART NUMBER | OUTPUT DRIVE | FREE SPEED | TORQUE RANGE | | | | AVERAGE AIR CONS. | | AIR CONS. @ LOAD | | OVERALL LENGTH | | NET WEIGHT | | AIR INLET |
|-------|-------------|--------------|------------|--------------|------|-------|------|-------------------|-----|------------------|-----|----------------|-----|------------|------|-----------|
| | | | | MIN. | | MAX | | cfm | l/s | cfm | l/s | in. | mm | lb | kg | NPTF |
| | | | | ft.lb | Nm | ft.lb | Nm | | | | | | | | | |
| CP782 | T025097 | 1/4 | 1,800 | 2.58 | 3.5 | 3.7 | 4.97 | 4 | 1.9 | 16 | 7.6 | 9.63 | 245 | 2.50 | 1.13 | 1/4" |
| CP783 | T025098 | 1/4 | 2,000 | 0.8 | 1.13 | 2.06 | 2.83 | 4 | 1.9 | 16 | 7.6 | 8.88 | 226 | 1.33 | 0.6 | 1/4" |

All models: Hose int. 3/8" (10 mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool.