

## Stack Caps

The exhaust stack cap is designed to be mounted on top of a vertical straight exhaust stack pipe and prevents water and debris from entering the stack. The stack cap is not water-tight during pressure washes or under strong wind conditions. Use zinc plated or chrome stack caps where exhaust gas temperatures are less than 900°F/482°C. For exhaust gas temperatures above 900°F/482°C, use 304 stainless steel stack caps.

For proper installation, the exhaust cap needs clearance for counterweight rotation and should be installed at a point that allows for this without interference.

The exhaust cap should be placed on the outer diameter of the stack pipe. Allow approximately ¼" of clearance between cap and top of stack.

O.D. Pipe Size in	mm	Zinc Plated	Chrome	304 Stainless
1.50	38	P270530		
1.75	44	P270531		
2.00	51	P270532		M002480
2.25	57	P270533		
2.50	64	P270534		M002482
2.75	70	P270535		
3.00	76	P270536	P271507	M002484
3.50	89	P270538	P271508	M002485
4.00	102	P270539	P270837	M002486
4.50	114	P270540		M002487
5.00	127	P270541	P270838	M002488
5.50	140	P270542		
6.00	152	P270543	P271511	M002490
8.00	203			M002491

**P270539 - Zinc Plated**



**P270837 - Chrome**



- Single bolt mount
- Nylon stop for quiet operation (zinc and chrome only)
- All metal construction (304 stainless steel only)

## Universal Swivel Hanger


- Heavy reinforced rubber pad
- Double pivot design improves flexibility and installation
- One piece construction installs in seconds
- 11 gauge cold rolled steel construction



**P206507 - 9" length**  
**J008167 - 13" length**

## Universal Mounting Bracket

- For 4" (102 mm) and (127 mm) pipes
- 3/8"-16 UNC-2A(4)
- Heavy gauge hot rolled steel construction
- Expands to 10" (254mm)



**P207784**

## Pipe Hangers

- Pre-punched holes (0.41" dia.) for easy installation
- 12 gauge hot rolled steel construction
- 12" overall bar length, width 0.88"
- 3/8"-16 UNC bolts/nuts included

### Pipe Hangers

Pipe Dia. in	mm	Part Number
3.00	76	P206523
3.50	89	P206524
4.00	102	P206525
5.00	127	P206526

