

**NYLON GREASE WHIPS**



3/16" I.D. Thermoplastic, fiber reinforced hose with 1/8 steel male pipe couplings. This hose combines the best features of conventional rubber hose with the unique advantages of synthetic materials.

**Recommended use:** Hand held grease guns.

PART No.	Length (IN.)	Working Pressure (P.S.I.)	Burst Pressure (PSI)
GWN-3-12	12	3000	12,000
GWN-3-18	18	3000	12,000
GWN-3-24	24	3000	12,000

Available packaged, Suffix PART No. with the letter "P"

**RUBBER GREASE WHIPS**



These assemblies are manufactured from 3/16" I.D. S.A.E. 100R1 rubber hose. The one braid hose is permanently crimped with 1/8 brass male pipe couplings on both ends. **Recommended use:** Hand held grease guns.

PART No.	Length (IN.)	Working Pressure (P.S.I.)	Burst Pressure (PSI)
GWR-3-12	12	3000	12,000
GWR-3-18	18	3000	12,000
GWR-3-24	24	3000	12,000
GWR-3-28	28	3000	12,000
GWR-3-36	36	3000	12,000
GWR-3-48	48	3000	12,000
GWR-3-54	54	3000	12,000
GWR-3-60	60	3000	12,000
GWR-3-72	72	3000	12,000
GWR-3-84	72	3000	12,000
GWR-3-96	96	3000	12,000
GWR-3-132	132	3000	12,000
GWR-3-144	144	3000	12,000



Available packaged, Suffix PART No. with the letter "P"

**D.O.T. AIR SHIFT TRANSMISSION ASSEMBLIES**



**Male Pipe Swivel**

**Male Pipe Thread**

PART No.	Swivel Pipe	Male Pipe	Hose I.D. (IN.)	Length (IN.)
2815-4-2	1/8	1/8	1/4	15
2831-4-2	1/8	1/8	1/4	31
2832-4-2	1/8	1/8	1/4	32
2834-4-2	1/8	1/8	1/4	34
2836-4-2	1/8	1/8	1/4	36

OTHER LENGTHS AVAILABLE ON REQUEST

**FIFTH WHEEL SLIDER ASSEMBLY**



- **MEETS:** S.A.E. J884D TYPE 3A D.O.T. F.M.V.S.S. 106
- **COLOR:** Black
- **TEMPERATURE:** -40°F to +200°F, -40°C to +93°C
- **FITTINGS:** 360° Brass working male pipe swivel each end.

Complete Kit see below  
Fifth Wheel Cylinder (Page 248)

PART No.	Working Length (IN.)	Tube O.D. (IN.)	Pigtail Length (IN.)	Male Pipe Ends
1486S-4-10	70	1/4	4	1/4

**FIFTH WHEEL SLIDER KIT**



**PART No. FWSK-1**

Designed for use on sliding fifth wheels, this kit includes most everything you need to complete the connections.

- Kit Includes:
- 70" Working Length of 1/4" O.D. S.A.E. - J844-A coiled air tube.
  - 360° Brass working male pipe swivels each end.
  - Spring guard hose end protectors.
  - 90° Brass adapter elbow.
  - Frame mounting terminal bolt.

**PART No. FWSK-2**

Same as above with Push-To-Connect style connections.

**AIR SEAT GUN SPLICER KIT**



**PART No. ASGK-1**

Simply splice the air seat line with the push-to-connect tee end of the assembly. This handy kit features an industrial air gun for cleaning out the cab on site.

- Kit Includes:
- 70" Working Length of 1/4" O.D. S.A.E. J844-A coiled air tube.
  - One 360° Brass working male pipe swivel.
  - Two spring guard hose end protectors.
  - Push-to-connect splicer tee. (No tools required)
  - Chrome plated, lever handle air gun.