

## ELECTRIC PUMPS FOR SPECIALTY FLUIDS

Electric diaphragm pumps for use with Windshield wash solution, antifreeze solution and DEF. Pump wetted materials are manufactured in EPDM, PP, PA and HNBR. Pumps are self priming pumps and have no seals in the pump shaft. Electric motor is protected with a 5 minute auto shut off function once the dispense valve is closed. NOT FOR USE WITH LUBRICANTS.

**560 215**



**560 212**



**560 224**



TECHNICAL DATA			
Part No.	560 215	560 212	560 224
Maximum delivery	8 gal/min	8 gal/min	8 gal/min
Max. working pressure	23 psi	23 psi	23 psi
Inlet & Outlet ports	1" BSPP	1" BSPP	1" BSPP
Voltage	115 VAC	12 VDC	24 VDC
Maximum current	2 amp	13 amp	22 amp
Motor protection	IP55 <sup>(1)</sup>	IP55 <sup>(1)</sup>	IP55 <sup>(1)</sup>
Accessories	60" power cord with three prong plug and off/on switch	60" power cord with crocodile clamps and off/on switch	60" power cord with crocodile clamps and off/on switch
Manual	856 809	856 810	856 810

(1) IP55, valid for outdoor use.

**NOTE:** Electric diaphragm pumps have BSPP male threads outlet and inlet. Use the following adaptors:

**Part No. 609 056**  
Converts to 1/2" hose barb.

**Part No. 609 072**  
Converts to 3/4" hose barb.

**Part No. 609 073**  
Converts to 1" hose barb.

Product specifications are subject to change without prior notice